

Water Quality Sampling Report

U.S. Army Corps of Engineers Omaha District

Additional Sediment/Soil Sampling Conducted at the Little Sioux Bend Shallow Water Habitat Project Site during October 2013



maintaining the data needed, and coincluding suggestions for reducing	ection of information is estimated to ompleting and reviewing the collect this burden, to Washington Headqu ald be aware that notwithstanding and OMB control number.	tion of information. Send comment parters Services, Directorate for Inf	s regarding this burden estimate ormation Operations and Reports	or any other aspect of the state of the stat	nis collection of information, Highway, Suite 1204, Arlington		
1. REPORT DATE NOV 2013		2. REPORT TYPE		3. DATES COVERED 00-00-2013 to 00-00-2013			
4. TITLE AND SUBTITLE				5a. CONTRACT	NUMBER		
Additional Sedimer	nt/Soil Sampling Co oitat Project Site du		de Sioux Bend	5b. GRANT NUM	MBER		
Shahow water Hai	mai Project Site du	iring October 2013		5c. PROGRAM I	ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NU	JMBER		
				5e. TASK NUME	BER		
				5f. WORK UNIT NUMBER			
	ZATION NAME(S) AND AI f Engineers,Omaha Z,68102	` '	itol	8. PERFORMING REPORT NUMB	G ORGANIZATION ER		
9. SPONSORING/MONITO	RING AGENCY NAME(S) A	AND ADDRESS(ES)		10. SPONSOR/M	ONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)			
12. DISTRIBUTION/AVAIL Approved for publ		ion unlimited					
13. SUPPLEMENTARY NO	TES						
14. ABSTRACT							
15. SUBJECT TERMS							
16. SECURITY CLASSIFIC	ATION OF:		17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON		
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	136	ALDI OLUBELI EROUN		

Report Documentation Page

Form Approved OMB No. 0704-0188

Water Quality Sampling Report

Additional Sediment/Soil Sampling Conducted at the Little Sioux Bend Shallow Water Habitat Project Site during October 2013

Prepared by:

Water Quality Unit
Water Control and Water Quality Section
Hydrologic Engineering Branch
Engineering Division
Omaha District
U.S. Army Corps of Engineers

November 2013

TABLE OF CONTENTS

EXECUTIVE SUMMARY	Page iv
1 BACKGROUND INFORMATION	
1.1 Project Description	
1.3 Section 404 Permitting Requirements – 404(b)(1) Guidelines	
1.4 Section 401 Water Quality Certification	
1.5 Reporting of Water Quality Considerations and Factual Determinations	
2 SAMPLING AND ANALYSIS METHODS	
2.1 Sampling and Analysis Plan	
2.2 Collection of Sediment/Soil Samples	
3 RESULTS	
3.1 Physical and Aggregate Properties	
3.2 Nutrients	
4 DISCUSSION	
4.1 Comparison of Nutrient Levels Measured at the Proposed Little Sioux project Site	30
4.1.1 Total Phosphorus	
4.1.2 Total Kjeldahl Nitrogen (TKN)	
4.1.3 Nitrate-Nitrite Nitrogen	
4.2 Nutrient Tonnage Associated with Suggested Disposal of Sediment/Soil Property Excavation at the Little Sioux Project Area	osed for
4.2.1 Estimated Amount of Material to be Excavated at the Little Sioux Project	42
4.2.2 Estimated Nutrient Conditions of the Three Proposed Depth Excavation La	ayers42
4.2.3 Estimation of the Nutrient Tonnage Associated with the Three Proposed D	epth
Excavation Layers	43
4.2.4 Comparison of Estimated Phosphorus Tonnage of Excavated Material to E Conditions in the Missouri River and Gulf of Mexico	
4.3 Comparison of Total Phosphorus Levels Measured at the Proposed Little Sioux Area to Total Phosphorus Levels Present in Off-Site Soils	•
4.3.1 Phosphorus in Iowa Soils	44
4.3.2 Phosphorus in Wisconsin Soils	46
4.3.3 Total Phosphorus Levels measured at the Proposed Little Sioux project Sit	e47
5 REFERENCES	47
Attachment 1. Sampling and Analysis Plan Addendum	
Attachment 2. Particle Size Distribution Reports Collected Sediment/Soil Samples	
Attachment 3. Laboratory Analytical Results for Collected Sediment/Soil Samples	
Attachment 4. Phosphorus in Iowa Soils	

EXECUTIVE SUMMARY

The U.S. Army Corps of Engineers (USACE) is proposing a project to construct shallow-water habitat (SWH) along the Little Sioux Bend of the Missouri River between RM666 and RM669. The construction of SWH will enhance the aquatic habitat of the Missouri River and benefit the endangered pallid sturgeon (Scaphirhynchus albus) population. Although on the Nebraska side of the Missouri River, the project area is located in Harrison County, Iowa and Burt County, Nebraska and will basically run down the old river channel that is the legal boundary between the States of Iowa and Nebraska. The USACE is proposing to use hydraulic dredging to excavate sediment/soil from the old river channel and discharge the dredge spoil to the Missouri River adjacent to the proposed project area. Section 404 of the Federal Clean Water Act (CWA) requires that a §404 permit be appropriately obtained prior to the discharge of any dredge or fill material into waters of the United States. Under §401 of the Federal CWA an applicant for a federal license or permit (i.e. §404 permit) must obtain a certification that the discharge and activity is consistent with appropriate State or Tribal water quality regulations. Regarding the Little Sioux project, a §401 water quality certification has been requested from the Iowa Department of Natural Resources (IDNR) and Nebraska Department of Environmental Quality (NDEQ) regarding compliance with State water quality standards and implementation plans. The Water Quality Sampling Report and Factual Determinations, "Results of Sediment Sampling and Elutriate Testing at the Proposed Little Sioux Bend Shallow Water Habitat Project Site" (USACE, April 2013) was previously prepared to support Section 404 permitting and State §401certification considerations at the proposed Little Sioux project. Subsequent to that report and conducted sediment sampling, the State of Iowa expressed concerns that the proposed hydraulic dredging to construct SWH at the Little Sioux project may lead to unacceptable nutrient loading to the Missouri River. An expressed concern was that the conducted sediment/soil sampling was not extensive enough (both spatially and depth of sampling) to allow nutrient loading questions to be adequately assessed. Additional sediment/soil sampling was conducted by the USACE at the proposed Little Sioux project site to further address the concerns expressed by the IDNR. The collected sediment/soil samples were analyzed for particle size, total phosphorus, total Kieldahl nitrogen, and nitrate-nitrite nitrogen.

Thirty-seven sediment/soil samples were collected among eight sampling locations at the proposed Little Sioux project site on 16 and 21-October-2013. Sediment/soil core samples were collected and composited every 2 feet to a depth of 10 feet where possible. Sampling depth was limited to 8 and 6 feet, at two of the sites due to the collapse of the bore hole in saturated soils below the water table – resulting in the collection of the 37 additional sediment/soil samples. The composition of the 37 collected sediment/soil samples ranged from 42.4 to 91.1 percent sand (8.9 to 57.6 percent fines) and averaged 73.6 percent sand (26.4 percent fines). Nutrient levels measured in the 37 collected sediment/soil samples ranged from 271 to 624 mg/kg (430 mg/kg average) total phosphorus, 52 to 1,070 mg/kg (282 mg/kg average) total Kjeldahl nitrogen, and non-detectable to 2.6 mg/kg (non-detectable 75th percentile) nitratenitrite nitrogen.

The measured nutrient levels were statistically-tested for significant differences ($\alpha=0.05$) between sampling location and depth. Regarding the measured total phosphorus levels, there was a significant difference among sampling sites, but no significant difference with sample depth. Regarding measured total Kjeldahl nitrogen levels, there was a significant difference among sampling sites, but no significant difference with sample depth. Regarding nitrate-nitrite nitrogen, there was no significant difference among sampling sites and with sampled depth. It is noted nitrate-nitrite nitrogen was nearly significantly different with depth.

The total tonnage of nutrients likely present in the sediment/soil proposed for excavation at the Little Sioux project area was estimated from the measured sediment/soil nutrient levels and the design excavation volumes. It is estimated that the total 430,000 CY of sediment/soil to be excavated at the proposed Little Sioux project area contains 236 tons of total phosphorus, 145 tons of total Kjeldahl nitrogen, and less than 1 ton of nitrate-nitrite nitrogen. The estimated total nutrient tonnage was appropriately allocated, based on design excavation volumes, to the three depth layers (i.e. 0-3 feet, 3-6 feet, and > 6 feet) that have been proposed by the IDNR for alternative disposal. The total phosphorus tonnage estimated to be in the three layers is 71.3 tons (0-3 feet), 57.4 tons (3-6 feet), and 107.7 tons (>6 feet).

The National Research Council of the National Academies published the report, "Missouri River Planning – Recognizing and Incorporating Sediment Management" which assessed nutrient loadings to the Missouri River and Gulf of Mexico (NRC, 2011). The report concluded that potential nitrogen loading from hydraulic dredging to construct SWH along the Missouri River was likely not a concern, but total phosphorus loadings could be a concern regarding Gulf of Mexico hypoxia. Currently, the total phosphorus load to the Gulf of Mexico is estimated to be 154,300 metric tons per year, with the contribution of the Missouri River to this total load estimated to be between 16.8% and 20% (NRC, 2011). Assuming the proposed SWH construction at the Little Sioux project area would be completed within one year, the total phosphorus tonnage in the proposed 430,000 CY to be excavated represents 0.76% of the current yearly total phosphorus loading in the Missouri River, and 0.14% of the annual total phosphorus load delivered to the Gulf of Mexico. These percentages are upper bound estimates, as sediment deposition processes in the Missouri and Mississippi River channels would reduce total phosphorus loads delivered to the Gulf, and actual downstream deliveries would be significantly less than these values.

Total phosphorus in Iowa soils tends to be higher in the surface horizon, decreases to a minimum and then increases with depth within members of the biosequence (Fenton, 1999). The general trend of the distribution is similar whether the parent material is loess or glacial till (Fenton 1999). The total phosphorus levels measured in the collected sediment/soil samples at the proposed Little Sioux project area are within the range of expected values based on soils and land use present at the project site, and exhibit a similar relationship with depth as indicated for Iowa soils by Fenton, 1999.

1 BACKGROUND INFORMATION

1.1 Project Description

A project is being proposed to create shallow-water habitat (SWH) along the Missouri River in Harrison County, Iowa and Burt County, Nebraska. The U.S. Army Corps of Engineers (USACE) is constructing SWH along the lower Missouri River downstream of Gavins Point Dam to mitigate aquatic habitat lost from past bank stabilization and channelization. Increasing SWH will enhance the endangered pallid sturgeon (*Scaphirhynchus albus*) population along the lower Missouri River. The District is referring to the proposed project as the Little Sioux project. Hydraulic dredging is being proposed to excavate sediment/soil from an old chute area of the Missouri River to create SWH. The material to be dredged is believed to be primarily sands and silts with some clays. It is proposed that the dredge spoil be discharged to the Missouri River adjacent to the proposed project area.

1.2 Project Location

The project area is located in Harrison County, Iowa and Burt County, Nebraska along the Little Sioux Bend of the Missouri River between RM666 and RM669. The project area is on the Nebraska side of Missouri River and will basically run down the old river channel that is the legal boundary between the States of Iowa and Nebraska (Figure 1). Figure 2 shows the proposed area for excavation to create SWH at the Little Sioux project area.




Figure 1. Location of proposed Little Sioux project site along the Missouri River west of Little Sioux, Iowa. (*Imagery Date: 18-July-2012, Google Earth*)




Figure 2. Proposed excavation to create shallow-water habitat at the Little Sioux project area.

1.3 Section 404 Permitting Requirements – 404(b)(1) Guidelines

Section 404 of the Federal Clean Water Act (CWA) requires that a §404 permit be appropriately obtained prior to the discharge of any dredge or fill material into waters of the United States. The issuance of §404 permits is pursuant to the Section 404(b)(1) Guidelines for Specification of Disposal Sites for Dredged or Fill Material (404(b)(1) Guidelines) [40 CFR Ch. I (7-1-10 Edition)]. Fundamental to the 404(b)(1) Guidelines is the precept that dredged or fill material should not be discharged into the aquatic ecosystem, unless it can be demonstrated that such a discharge will not have an unacceptable adverse impact either individually or in combination with known and/or probable impacts of other activities affecting the ecosystems of concern. No discharge of dredged or fill material is permitted: 1) if it will cause or contribute, after consideration of disposal site dilution and dispersion, to violations of any applicable State water quality standard; 2) if it will cause or contribute to significant degradation of the waters of the United States; or 3) unless appropriate and practicable steps have been taken which will minimize potential adverse impacts of the discharge on the aquatic system.

Compliance with the 404(b)(1) Guidelines is based, in part, on "Factual Determinations" of the potential impact of the proposed dredge and fill on the aquatic environment. The \$404 permitting authority is required to determine in writing the potential short-term or long-term effects of a proposed discharge of dredged or fill material on the physical, chemical, and biological components of the aquatic

environment. These Factual Determinations are used in making findings of compliance or non-compliance with the restrictions on discharge. The 404(b)(1) Guidelines at §230.11 identify the following eight Factual Determinations that are to be made on the effects of each proposed discharge of dredge and fill material:

- 1) Physical substrate determinations.
- 2) Water circulation, fluctuation, and salinity determinations.
- 3) Suspended particulate/turbidity determinations.
- 4) Contaminant determinations.
- 5) Aquatic ecosystem and organism determinations.
- 6) Proposed disposal site determinations.
- 7) Determination of cumulative effects on the aquatic ecosystem.
- 8) Determination of secondary effects on the aquatic ecosystem.

The intent of this report is to provide additional information to support Factual Determinations of the potential water quality impacts of hydraulic dredging discharge at the proposed Little Sioux project on the Missouri River. As defined in the Federal CWA and USACE Regulation No. 1110-2-8154, water quality is defined as the physical, chemical, and biological characteristics of water.

1.4 Section 401 Water Quality Certification

Under §401 of the Federal CWA an applicant for a federal license or permit (i.e. §404 permit) must obtain a certification that the discharge and activity is consistent with State or Tribal effluent limitations (CWA §301), water quality related effluent limitations (CWA §302), water quality standards and implementation plans (CWA §303), national standards of performance (§306), toxic and pretreatment effluent standards (CWA §307) and "any other appropriate requirement of State or Tribal law set forth in such certification." Regarding the Little Sioux project, a §401 water quality certification will be requested from the Iowa Department of Natural Resources (IDNR) and Nebraska Department of Environmental Quality (NDEQ) regarding compliance with State water quality standards and implementation plans. It is noted that the State of Iowa has recently released the "Iowa Nutrient Reduction Strategy – A science and technology-based framework to assess and reduce nutrients to Iowa waters and the Gulf of Mexico".

1.5 Reporting of Water Quality Considerations and Factual Determinations

The Water Quality Sampling Report and Factual Determinations, "Results of Sediment Sampling and Elutriate Testing at the Proposed Little Sioux Bend Shallow Water Habitat Project Site" (USACE, April 2013) was previously prepared to support Section 404 permitting and State §401certification considerations at the proposed Little Sioux project. Subsequent to that report, and the conducted sediment sampling at the proposed Little Sioux project site, the State of Iowa expressed concerns that the proposed hydraulic dredging to construct SWH at the Little Sioux project may lead to unacceptable nutrient loading to the Missouri River. An expressed concern was that the conducted sediment/soil sampling was not extensive enough (both spatially and depth of sampling) to allow nutrient loading questions to be adequately assessed. The information provided in this report is meant to further address this concern.

2 SAMPLING AND ANALYSIS METHODS

Additional sediment/soil samples, representative of the areas to be excavated for SWH construction at the proposed Little Sioux project site, were collected and analyzed.

2.1 Sampling and Analysis Plan

A Sampling and Analysis Plan (SAP) addendum to the previously implemented SAP was developed to collect and analyze additional sediment/soil samples at the proposed Little Sioux project site. The SAP addendum was developed to increase the available information on the spatial and depth variability of nutrient conditions of the sediment/soil in the areas proposed for excavation at the Little Sioux project site. The SAP addendum was implemented as written, with one modification, and is included as Attachment 1. The one modification was that percent solids was also analyzed and reported for the collected sediment/soil samples. The parameters that were analyzed in the laboratory for the collected sediment/soil samples are listed in Table 1.

Table 1. Parameters analyzed in the laboratory f	for the collected sediment/soil samples.
---	--

Parameter	Method	Detection Limit	
PHYSICAL AND AGGREGATE PROPERTIES			
Particle Size	Sieve (Minimum Sieve #200)	0.001 mm	
Percent Solids	SM 2540G	0.01%	
NUTRIENTS			
Nitrogen, Kjeldahl Total as N	EPA 351.3	0.2 mg/kg	
Nitrogen, Nitrate/Nitrite Total as N	EPA 353.2	0.02 mg/kg	
Phosphorus, Total	SM 4500PF	0.02 mg/kg	

2.2 <u>Collection of Sediment/Soil Samples</u>

Thirty-seven sediment/soil samples were collected among eight sampling locations at the proposed Little Sioux project site on 16 and 21-October-2013. The eight sampling locations (i.e. sites LS-D1, LS-D2, LS-D3, LS-D4, LS-D5, LS-D6, LS-D7, and LS-D8) where the sediment/soil samples were collected are shown on Figures 3 through 5 and described in Tables 2 and 3. The sediment/soil samples at each of the eight sites were collected with a gas-powered auger equipped with a 3¼-inch diameter stainless steel coring bit. Core samples were collected and composited every 2 feet to a depth of 10 feet where possible. Sampling depth was limited to 8 and 6 feet, respectively, at sites LS-D2 and LS-D5 due to the collapse of the bore hole in saturated soils below the water table.

3 RESULTS

3.1 Physical and Aggregate Properties

Tables 4 through 12 provide a summary of the particle size and percent solids conditions determined for the 37 collected sediment/soil samples at sites LS-D1, LS-D2, LS-D3, LS-D4, LS-D5, LS-D6, LS-D7, and LS-D8. Figures 6 through 13 plot the same information. Attachment 2 provides the Particle Size Distribution Reports prepared by Midwest Laboratories for the collected sediment/soil samples.

3.2 **Nutrients**

Tables 13 through 20 provide a summary of the nutrient conditions determined for the 37 collected sediment/soil samples at sites LS-D1, LS-D2, LS-D3, LS-D4, LS-D5, LS-D6, LS-D7, and LS-D8. Figures 14 through 21 plot the same information. Attachment 3 provides the nutrient data as analyzed by Midwest Laboratories (Omaha, Nebraska) for the collected sediment/soil samples.




Figure 3. Location of the eight sites where soil/sediment samples were collected for additional analyses at the Lower Sioux Bend SWH project site on 16 and 21 October 2013. (*Imagery Date: 18-Jul-2012*)



Figure 4. Approximate locations of sites LS-D1, LS-D2, LS-D3, and LS-D4 where additional soil/sediment samples were collected at the Little Sioux Bend SWH project site on 21-October-2013. (*Imagery Date: Nov-2013*)



Figure 5. Approximate locations of sites LS-D5, LS-D6, LS-D7, and LS-D8 where additional soil/sediment samples were collected at the Little Sioux Bend SWH project site on 16 and 21-October-2013. (*Imagery Date: Nov-2013*)

Table 2. Additional sediment/soil samples collected at the proposed Little Sioux project site.

Sampling Site	Sample ID	Sampled Depth	Date, Time	Sample Type
	LS-D1A	0 – 2 feet	21-Oct-13, 14:30	Composite Core
	LS-D1B	2 – 4 feet	21-Oct-13, 14:30	Composite Core
LS-D1	LS-D1C	4 – 6 feet	21-Oct-13, 14:30	Composite Core
	LS-D1D	6 – 8 feet	21-Oct-13, 14:30	Composite Core
	LS-D1E	8 – 10 feet	21-Oct-13, 14:30	Composite Core
	LS-D2A	0 – 2 feet	21-Oct-13, 13:10	Composite Core
LS-D2	LS-D2B	2 – 4 feet	21-Oct-13, 13:10	Composite Core
L3-D2	LS-D2C	4 – 6 feet	21-Oct-13, 13:10	Composite Core
	LS-D2D	6 – 8 feet	21-Oct-13, 13:10	Composite Core
	LS-D3A	0 – 2 feet	21-Oct-13, 12:30	Composite Core
	LS-D3B	2 – 4 feet	21-Oct-13, 12:30	Composite Core
LS-D3	LS-D3C	4 – 6 feet	21-Oct-13, 12:30	Composite Core
	LS-D3D	6 – 8 feet	21-Oct-13, 12:30	Composite Core
	LS-D3E	8 – 10 feet	21-Oct-13, 12:30	Composite Core
	LS-D4A	0 – 2 feet	21-Oct-13, 11:50	Composite Core
	LS-D4B	2 – 4 feet	21-Oct-13, 11:50	Composite Core
LS-D4	LS-D4C	4 – 6 feet	21-Oct-13, 11:50	Composite Core
	LS-D4D	6 – 8 feet	21-Oct-13, 11:50	Composite Core
	LS-D4E	8 – 10 feet	21-Oct-13, 11:50	Composite Core
	LS-D5A	0-2 feet	21-Oct-13, 10:20	Composite Core
LS-D5	LS-D5B	2 – 4 feet	21-Oct-13, 10:20	Composite Core
	LS-D5C	4 – 6 feet	21-Oct-13, 10:20	Composite Core
	LS-D6A	0 – 2 feet	21-Oct-13, 9:30	Composite Core
	LS-D6B	2 – 4 feet	21-Oct-13, 9:30	Composite Core
LS-D6	LS-D6C	4 – 6 feet	21-Oct-13, 9:30	Composite Core
	LS-D6D	6 – 8 feet	21-Oct-13, 9:30	Composite Core
	LS-D6E	8 – 10 feet	21-Oct-13, 9:30	Composite Core
	LS-D7A	0 – 2 feet	16-Oct-13, 15:00	Composite Core
	LS-D7B	2 – 4 feet	16-Oct-13, 15:00	Composite Core
LS-D7	LS-D7C	4 – 6 feet	16-Oct-13, 15:00	Composite Core
	LS-D7D	6 – 8 feet	16-Oct-13, 15:00	Composite Core
	LS-D7E	8 – 10 feet	16-Oct-13, 15:00	Composite Core
	LS-D8A	0 – 2 feet	16-Oct-13, 13:00	Composite Core
	LS-D8B	2 – 4 feet	16-Oct-13, 13:00	Composite Core
LS-D8	LS-D8C	4 – 6 feet	16-Oct-13, 13:00	Composite Core
	LS-D8D	6 – 8 feet	16-Oct-13, 13:00	Composite Core
	LS-D8E	8 – 10 feet	16-Oct-13, 13:00	Composite Core

Table 3. Geo-references locations where additional sediment/soil samples were collected at the proposed Little Sioux project site.

Site	Latitude	Longitude	Depth to Water Table
LS-D1	41° 47' 17.7"	96° 04' 02.7"	5 feet
LS-D2	41° 47′ 10.3″	96° 04' 03.4"	3 feet
LS-D3	41° 47' 04.2"	96° 04' 10.7"	>10 feet
LS-D4	41° 46' 58.8"	96° 04' 17.0''	9 feet
LS-D5	41° 46' 50.6"	96° 04' 20.6''	3 feet
LS-D6	41° 46' 44.2"	96° 04' 27.6''	3 feet
LS-D7	41° 46' 39.1"	96° 04' 31.3"	6 feet
LS-D8	41° 46′ 33.5″	96° 04' 32.5"	6 feet

Table 4. Summary of particle size and percent solids analyses of the sediment/soil samples collected at site LS-D1 at the proposed Little Sioux project site.

Sample	% Gravel		ravel	% Sand			% F		
ID	% Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay	% Solids
LS-D1A (0-2 ft)	0.0	0.0	0.0	0.1	7.2	79.9	11.8	1.0	92.9
LS-D1B (2-4 ft)	0.0	0.0	0.0	0.5	36.3	58.3	3.9	1.0	95.7
LS-D1C (4-6 ft)	0.0	0.0	0.0	0.1	13.3	71.5	13.7	1.4	82.2
LS-D1D (6-8 ft)	0.0	0.0	0.0	0.0	5.0	42.1	48.9	4.0	75.6
LS-D1E (8-10 ft)	0.0	0.0	0.0	0.0	6.2	61.2	30.5	2.1	75.7
MEAN	0.0	0.0	0.0	0.1	13.6	62.6	21.8	1.9	84.4

Depth to groundwater = 5 feet.

See Table 12 for definition of particle sizes.

Table 5. Summary of particle size and percent solids analyses of the sediment/soil samples collected at site LS-D2 at the proposed Little Sioux project site.

Sample		% Gravel		% Sand			% F		
ID	% Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay	% Solids
LS-D2A (0-2 ft)	0.0	0.0	0.0	0.0	0.3	32.9	55.2	11.6	82.8
LS-D2B (2-4 ft)	0.0	0.0	0.0	0.0	0.1	61.0	36.1	2.8	73.1
LS-D2C (4-6 ft)	0.0	0.0	0.0	0.0	0.2	72.5	25.4	1.9	74.0
LS-D2D (6-8 ft)	0.0	0.0	0.0	0.0	0.1	88.9	10.0	1.0	73.8
MEAN	0.0	0.0	0.0	0.0	0.2	63.8	31.7	4.3	78.4

Depth to groundwater = 3 feet.

Only collected sediment/soil sample to a depth of 8 feet – bore hole side walls collasped in saturated zone. See Table 12 for definition of particle sizes.

Table 6. Summary of particle size and percent solids analyses of the sediment/soil samples collected at site LS-D3 at the proposed Little Sioux project site.

Sample	% Gravel			% Sand			% Fines		
ID	% Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay	% Solids
LS-D3A (0-2 ft)	0.0	0.0	0.0	0.0	0.1	38.8	53.2	7.9	87.6
LS-D3B (2-4 ft)	0.0	0.0	0.0	0.0	2.0	86.4	10.6	1.0	95.9
LS-D3C (4-6 ft)	0.0	0.0	0.0	0.0	1.3	95.1	2.3	1.3	97.7
LS-D3D (6-8 ft)	0.0	0.0	0.0	0.0	1.2	95.4	2.1	1.3	97.1
LS-D3E (8-10 ft)	0.0	0.0	0.0	0.0	1.5	92.4	4.8	1.3	90.6
MEAN	0.0	0.0	0.0	0.0	1.2	81.6	14.6	2.6	93.8

Depth to groundwater = >10 feet.

See Table 12 for definition of particle sizes.

Table 7. Summary of particle size and percent solids analyses of the sediment/soil samples collected at site LS-D4 at the proposed Little Sioux project site.

Sample		% G	ravel		% Sand			% Fines		
ID	% Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay	% Solids	
LS-D4A (0-2 ft)	0.0	0.0	0.0	0.0	4.7	50.1	33.7	11.5	90.9	
LS-D4B (2-4 ft)	0.0	0.0	0.4	0.1	5.4	88.8	4.0	1.3	97.3	
LS-D4C (4-6 ft)	0.0	0.0	0.0	0.0	4.3	92.1	2.6	1.0	97.1	
LS-D4D (6-8 ft)	0.0	0.0	0.0	0.0	6.7	89.7	2.2	1.4	90.0	
LS-D4E (8-10 ft)	0.0	0.0	0.0	0.0	4.6	87.9	6.5	1.0	76.1	
MEAN	0.0	0.0	0.1	0.0	5.1	81.7	9.8	3.2	90.3	

Depth to groundwater = 9 feet.

See Table 12 for definition of particle sizes.

Table 8. Summary of particle size and percent solids analyses of the sediment/soil samples collected at site LS-D5 at the proposed Little Sioux project site.

Sample		% G	ravel	% Sand			% F		
ID	% Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay	% Solids
LS-D5A (0-2 ft)	0.0	0.0	0.0	0.0	4.5	76.3	15.5	3.7	83.0
LS-D5B (2-4 ft)	0.0	0.0	0.0	0.6	12.9	83.4	2.1	1.0	80.2
LS-D5C (4-6 ft)	0.0	0.0	0.0	0.0	5.7	90.6	2.7	1.0	78.7
MEAN	0.0	0.0	0.0	0.2	7.7	83.4	6.8	1.9	80.7

Depth to groundwater = 3 feet.

Only collected sediment/soil sample to a depth of 6 feet – bore hole side walls collasped in saturated zone. See Table 12 for definition of particle sizes.

Table 9. Summary of particle size and percent solids analyses of the sediment/soil samples collected at site LS-D6 at the proposed Little Sioux project site.

Sample	Sample		% Gravel		% Sand			% Fines	
ID	% Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay	% Solids
LS-D6A (0-2 ft)	0.0	0.0	0.0	0.0	3.0	64.1	23.8	9.1	91.1
LS-D6B (2-4 ft)	0.0	0.0	0.0	0.0	0.9	75.7	19.2	4.2	79.4
LS-D6C (4-6 ft)	0.0	0.0	0.0	0.0	0.8	24.7	57.1	17.4	72.7
LS-D6D (6-8 ft)	0.0	0.0	0.0	0.0	2.1	47.9	41.4	8.6	72.5
LS-D6E (8-10 ft)	0.0	0.0	0.0	0.0	3.4	58.2	30.7	7.7	76.6
MEAN	0.0	0.0	0.0	0.0	2.0	54.1	34.4	9.4	78.5

Depth to groundwater = 3 feet.

See Table 12 for definition of particle sizes.

Table 10. Summary of particle size and percent solids analyses of the sediment/soil samples collected at site LS-D7 at the proposed Little Sioux project site.

Sample		% Gravel		% Sand		% Fines			
ID	% Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay	% Solids
LS-D7A (0-2 ft)	0.0	0.0	0.0	0.0	0.4	68.3	27.7	3.6	86.1
LS-D7B (2-4 ft)	0.0	0.0	0.0	0.0	5.7	84.9	8.4	1.0	95.1
LS-D7C (4-6 ft)	0.0	0.0	0.0	0.3	27.0	69.2	2.5	1.0	96.3
LS-D7D (6-8 ft)	0.0	0.0	0.0	0.7	24.7	70.4	3.2	1.0	88.6
LS-D7E (8-10 ft)	0.0	0.0	0.0	0.3	18.4	75.7	4.6	1.0	80.0
MEAN	0.0	0.0	0.0	0.3	15.2	73.7	9.3	1.5	89.2

Depth to groundwater = 6 feet.

See Table 12 for definition of particle sizes.

Table 11. Summary of particle size and percent solids analyses of the sediment/soil samples collected at site LS-D8 at the proposed Little Sioux project site.

Sample		% G	ravel		% Sand		% F	ines	
ID	% Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay	% Solids
LS-D8A (0-2 ft)	0.0	0.0	0.0	0.0	0.2	57.1	33.9	8.8	85.2
LS-D8B (2-4 ft)	0.0	0.0	0.0	0.0	0.0	23.1	64.7	12.2	82.8
LS-D8C (4-6 ft)	0.0	0.0	0.0	0.0	0.0	53.1	41.1	5.8	89.2
LS-D8D (6-8 ft)	0.0	0.0	0.0	0.0	0.0	27.0	63.5	9.5	77.8
LS-D8E (8-10 ft)	0.0	0.0	0.0	0.0	0.0	51.9	44.2	3.9	76.3
MEAN	0.0	0.0	0.0	0.0	0.0	42.4	49.5	8.0	82.2

Depth to groundwater = 6 feet.

See Table 12 for definition of particle sizes.

Table 12. Size ranges for defined sediment/soil particle size cateogies.

	Gra	avel	Sand			Fines	
Cobbles	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay
	76,200μ	19,050μ	4,760μ	2,000μ	400μ	200μ	
$< 76,200 \mu$	to	to	to	to	to	to	> 2µ
	19,050μ	$4,760\mu$	2,000μ	400μ	200μ	2μ	
	76.2mm	19.1mm	4.8mm	2mm	0.4mm	0.2mm	
< 76.2mm	to	to	to	to	to	to	> 0.002mm
	19.1mm	4.8mm	2mm	0.4mm	0.2mm	0.002mm	




Figure 6. Percent particle size (dry wt.) and percent solids of depth-increment sediment/soil samples collected at site LS-D1.




Figure 7. Percent particle size (dry wt.) and percent solids of depth-increment sediment/soil samples collected at site LS-D2.




Figure 8. Percent particle size (dry wt.) and percent solids of depth-increment sediment/soil samples collected at site LS-D3.




Figure 9. Percent particle size (dry wt.) and percent solids of depth-increment sediment/soil samples collected at site LS-D4.




Figure 10. Percent particle size (dry wt.) and percent solids of depth-increment sediment/soil samples collected at site LS-D5.




Figure 11. Percent particle size (dry wt.) and percent solids of depth-increment sediment/soil samples collected at site LS-D6.

Percent Compostion of Sediment/Soil Samples Collected at Site LS-D7 10 20 30 40 50 60 70 80 90 100 0 0 - 2 2 - 4 ■Gravel - Fine Depth Interval (feet) ■Sand - Coarse ■Sand - Medium ■Sand - Fine ■Silt 4 - 6 **□Clay □% Solids** 6 - 8 8 - 10

Figure 12. Percent particle size (dry wt.) and percent solids of depth-increment sediment/soil samples collected at site LS-D7.




Figure 13. Percent particle size (dry wt.) and percent solids of depth-increment sediment/soil samples collected at site LS-D8.

Table 13. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D1 at the proposed Little Sioux project site.

Sample ID	Total Kjeldahl Nitrogen (mg/kg dry wt.)	Nitrate-Nitrite Nitrogen (mg/kg dry wt.)	Total Phosphorus (mg/kg dry wt.)
LS-D1A (0-2 ft)	205	1.1	380
LS-D1B (2-4 ft)	81	1.2	295
LS-D1C (4-6 ft)	159	1.3	370
LS-D1D (6-8 ft)	398	< 0.05	471
LS-D1E (8-10 ft)	223	< 0.05	435
MEAN	213	0.7	390

Depth to Groundwater = 5 feet.

Table 14. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D2 at the proposed Little Sioux project site.

Sample ID	Total Kjeldahl Nitrogen (mg/kg dry wt.)	Nitrate-Nitrite Nitrogen (mg/kg dry wt.)	Total Phosphorus (mg/kg dry wt.)
LS-D2A (0-2 ft)	1,070	2.3	576
LS-D2B (2-4 ft)	235	< 0.04	467
LS-D2C (4-6 ft)	349	< 0.05	500
LS-D2D (6-8 ft)	136	< 0.05	418
MEAN	448	0.6	490

Depth to Groundwater = 3 feet.

Only collected sediment/soil sampled to a depth of 8 feet – bore hole side walls collasped in saturated zone.

Table 15. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D3 at the proposed Little Sioux project site.

Sample ID	Total Kjeldahl Nitrogen (mg/kg dry wt.)	Nitrate-Nitrite Nitrogen (mg/kg dry wt.)	Total Phosphorus (mg/kg dry wt.)
LS-D3A (0-2 ft)	613	< 0.04	578
LS-D3B (2-4 ft)	195	< 0.04	381
LS-D3C (4-6 ft)	68	< 0.04	343
LS-D3D (6-8 ft)	74	< 0.04	332
LS-D3E (8-10 ft)	120	< 0.04	388
MEAN	214	<0.04	404

Depth to Groundwater = >10 feet.

Table 16. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D4 at the proposed Little Sioux project site.

Sample ID	Total Kjeldahl Nitrogen (mg/kg dry wt.)	Nitrate-Nitrite Nitrogen (mg/kg dry wt.)	Total Phosphorus (mg/kg dry wt.)
LS-D4A (0-2 ft)	681	< 0.04	519
LS-D4B (2-4 ft)	110	< 0.04	356
LS-D4C (4-6 ft)	52	< 0.04	331
LS-D4D (6-8 ft)	64	< 0.04	322
LS-D4E (8-10 ft)	77	< 0.05	318
MEAN	197	<0.05	369

Depth to Groundwater = 9 feet.

Table 17. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D5 at the proposed Little Sioux project site.

Sample ID	Total Kjeldahl Nitrogen (mg/kg dry wt.)	Nitrate-Nitrite Nitrogen (mg/kg dry wt.)	Total Phosphorus (mg/kg dry wt.)
LS-D5A (0-2 ft)	181	< 0.04	449
LS-D5B (2-4 ft)	73	< 0.04	294
LS-D5C (4-6 ft)	121	< 0.04	374
MEAN	125	<0.04	372

Depth to Groundwater = 3 feet.

Only collected sediment/soil sampled to a depth of 6 feet – bore hole side walls collasped in saturated zone.

Table 18. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D6 at the proposed Little Sioux project site.

Sample ID	Total Kjeldahl Nitrogen (mg/kg dry wt.)	Nitrate-Nitrite Nitrogen (mg/kg dry wt.)	Total Phosphorus (mg/kg dry wt.)
LS-D6A (0-2 ft)	563	1.5	481
LS-D6B (2-4 ft)	290	1.4	409
LS-D6C (4-6 ft)	769	< 0.05	624
LS-D6D (6-8 ft)	652	< 0.05	584
LS-D6E (8-10 ft)	387	< 0.05	516
MEAN	532	0.6	523

Depth to Groundwater = 3 feet.

Table 19. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D7 at the proposed Little Sioux project site.


Sample ID	Total Kjeldahl Nitrogen (mg/kg dry wt.)	Nitrate-Nitrite Nitrogen (mg/kg dry wt.)	Total Phosphorus (mg/kg dry wt.)
LS-D7A (0-2 ft)	143	< 0.04	461
LS-D7B (2-4 ft)	82	< 0.04	351
LS-D7C (4-6 ft)	75	< 0.04	276
LS-D7D (6-8 ft)	66	< 0.04	271
LS-D7E (8-10 ft)	65	< 0.04	332
MEAN	86	<0.04	338


Depth to Groundwater = 6 feet.

Table 20. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D8 at the proposed Little Sioux project site.

Sample ID	Total Kjeldahl Nitrogen (mg/kg dry wt.)	Nitrate-Nitrite Nitrogen (mg/kg dry wt.)	Total Phosphorus (mg/kg dry wt.)
LS-D8A (0-2 ft)	585	2.6	552
LS-D8B (2-4 ft)	499	2.4	575
LS-D8C (4-6 ft)	261	< 0.04	503
LS-D8D (6-8 ft)	440	< 0.05	575
LS-D8E (8-10 ft)	288	< 0.05	501
MEAN	415	1.0	541

Depth to Groundwater = 6 feet.










Figure 14. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D1.










Figure 15. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D2.










Figure 16. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D3.








Figure 17. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D4.




Figure 18. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D5.






Figure 19. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D6.










Figure 20. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D7.








Figure 21. Summary of nutrient analyses of the sediment/soil samples collected at site LS-D8.

4 DISCUSSION

4.1 Comparison of Nutrient Levels Measured at the Proposed Little Sioux Project Site

4.1.1 Total Phosphorus

A data matrix of the measured sediment/soil total phosphorus levels in the 37 samples collected among the eight sampling sites and five depth increments is provided in Table 21. Figure 22 provides a boxplot of the measured sediment/soil total phosphorus levels by sampling sites, and Figure 23 provides a boxplot of the measured sediment/soil total phosphorus levels by depth increment. Boxplots were constructed using the MINITAB statistical software.

Depth				Sit	te			
Increment (ft)	LS-D1	LS-D2	LS-D3	LS-D4	LS-D5	LS-D6	LS-D7	LS-D8
0 - 2	380	576	578	519	449	481	461	552
2 – 4	295	467	381	356	294	409	351	575
4 – 6	370	500	343	331	374	624	276	503
6 – 8	471	418	332	322	*	584	271	575
8 _ 10	435	*	388	318	*	516	332	501

Table 21. Data matrix for measured sediment/soil total phosphorus levels.

^{*} Grid cell not sampled due to bore hole collapse.




Figure 22. Boxplots of sediment/soil total phosphorus levels measured at the eight sampled sites. [Note: The box represents the middle 50% of the data. The line through the box represents the median. The lines (whiskers) extending from the box represent the upper and lower 25% of the data excluding outliers. Outliers, if present, are represented by asterisks (*). The red point on each plot represents the mean.]




Figure 23. Boxplots of sediment/soil total phosphorus levels measured at the eight sampled sites by the composited depth increments. [Note: See Figure 22 for explanation of boxplot. The red dashed line represents the total phosphorus depth profile plotted by connecting means of the depth increments.]

4.1.1.1 <u>Do Total Phosphorus Levels Significantly Vary Spatially and with Depth at the Proposed Little Sioux Project Area?</u>

The following hypotheses and alternative null hypotheses were tested:

- H₁₀: Total phosphorus levels measured at the eight sampled locations are significantly different.
- H1_a: Total phosphorus levels measured at the eight sampled locations are not significantly different.
- H2_o: Total phosphorus levels measured at different depth increments are significantly different i.e. measured total phosphorus levels are significantly different with depth.
- $H2_a$: Total phosphorus levels measured at different depth increments are not significantly different i.e. measured total phosphorus levels are not significantly different with depth.

4.1.1.2 <u>Two-Way Analysis of Variance (ANOVA)</u>

A Two-Way ANOVA with the response variable as total phosphorus and the two factors of site and depth increment was not able to be applied due to the missing depth increment data at site LS-D2 (8-10 feet) and site LS-D5 (6-8 and 8-10 feet) (Table 21).

4.1.1.3 One-Way ANOVA

A One-Way ANOVA was applied to the total phosphorus data matrix (Table 21). The response variable is total phosphorus and the factors evaluated separately are site and depth increment.

4.1.1.3.1 One-Way ANOVA Total Phosphorus versus Site

Table 22 provides the One-Way ANOVA results for total phosphorus versus site. Based on the premise that non-overlapping 95% confidence intervals indicate a significant difference, measured sediment/soil total phosphorus levels at 10 of the possible 28 comparisons of sites are significantly different (Table 23).

Table 22. One-way ANOVA results: Phosphorus versus Site

Mean

Source	DF	SS	MS	F	P
Site	7	201,119	28,743	4.90	0.001
Error	29	170,099	5,865		
Total	36	371,298			

Comparison of Sites:

N

Site

Individual 95% CIs For Mean Based on Pooled StDev

---+----+---

(*	67.29	390.20	5	LS-D1
(66.35	490.25	4	LS-D2
(*	99.96	404.40	5	LS-D3
(*)	85.03	369.20	5	LS-D4
(*	77.51	372.33	3	LS-D5
	84.75	522.80	5	LS-D6
(*)	76.92	338.20	5	LS-D7
(37.00	541.20	5	LS-D8
+				
300 400		76.59	ev =	Pooled StI
				-

StDev

Table 23. Comparison of measured sediment/soil total phosphorus levels at the eight sampled sites for significant differences.

	LS-D1	LS-D2	LS-D3	LS-D4	LS-D5	LS-D6	LS-D7
LS-D2	No						
LS-D3	No	No					
LS-D4	No	No	No				
LS-D5	No	No	No	No			
LS-D6	Yes	No	No	Yes	Yes		
LS-D7	No	Yes	No	No	No	Yes	
LS-D8	Yes	No	Yes	Yes	Yes	No	Yes

Note: No and Yes indicate the presence of a significant difference based on non-overlapping 95% confidence intervals.

4.1.1.3.2 One-Way ANOVA Total Phosphorus versus Depth Increment

Table 24 provides the One-Way ANOVA results for total phosphorus versus depth increment. Based on the premise that non-overlapping 95% confidence intervals indicate a significant difference, measured sediment/soil total phosphorus levels at none of the possible 10 comparisons of depth increments are significantly different (Table 25).

Table 24. One-way ANOVA results: Phosphorus versus Depth Increment.

Source	DF	SS	MS	F	P
Site	4	54,126	13,531	1.37	0.268
Error	32	317,172	9,912		
Total	36	371,298			

Comparison of Depth Increments:

Individual 95% CIs For Mean Based on Pooled StDev

Depth	N	Mean	StDev	+			+-
0-2	8	499.50	69.49		(*)
2-4	8	391.00	93.74	(*)	
4-6	8	415.13	115.83	(*)	
6-8	7	424.71	124.45	(*)	
8-10	6	415.00	83.69	(*)	
				+			+-
Pooled St	Dev =	99.56		350	420	490	560

Table 25. Comparison of measured sediment/soil total phosphorus levels at the five sampled depth increments for significant differences.

	0-2 ft	2 – 4 ft	4 -6 ft	6 – 8 ft
2 – 4 ft	No			
4 – 6 ft	No	No		
6 – 8 ft	No	No	No	
8 – 10 ft	No	No	No	No

Note: No and Yes indicate the presence of a significant difference based on non-overlapping inter-quartile ranges and 95% confidence intervals.

4.1.2 Total Kjeldahl Nitrogen (TKN)

A data matrix of the measured sediment/soil TKN levels in the 37 samples collected among the eight sampling sites and five depth increments is provided in Table 26. Figure 24 provides a boxplot of the measured sediment/soil TKN levels by sampling sites, and Figure 25 provides a boxplot of the measured sediment/soil TKN levels by depth increment. Boxplots were constructed using the MINITAB statistical software.

Depth				Sit	te			
Increment (ft)	LS-D1	LS-D2	LS-D3	LS-D4	LS-D5	LS-D6	LS-D7	LS-D8
0 - 2	205	1,070	613	681	181	563	143	585
2 – 4	81	235	195	110	73	290	82	499
4 – 6	159	349	68	52	121	769	75	261
6 – 8	398	136	74	64	*	652	66	440
Q 10	223	*	120	77	*	397	65	288

Table 26. Data matrix for measured sediment/soil Total Kjeldahl Nitrogen (TKN) levels.

^{*} Grid cell not sampled due to bore hole collapse.




Figure 24. Boxplots of sediment/soil Total Kjeldahl Nitrogen (TKN) levels measured at the eight sampled sites. [Note: The box represents the middle 50% of the data. The line through the box represents the median. The lines (whiskers) extending from the box represent the upper and lower 25% of the data excluding outliers. Outliers, if present, are represented by asterisks (*). The red point on each plot represents the mean.]




Figure 25. Boxplots of sediment/soil Total Kjeldahl Nitrogen (TKN) levels measured at the eight sampled sites by the composited depth increments. [Note: See Figure 24 for explanation of boxplot. The red dashed line represents the TKN depth profile plotted by connecting means of the depth increments.]

4.1.2.1 <u>Do TKN Levels Significantly Vary Spatially and with Depth at the Proposed Little Sioux project Area?</u>

The following hypotheses and alternative null hypotheses were tested:

- H₁₀: TKN levels measured at the eight sampled locations are significantly different.
- H_{1a}: TKN levels measured at the eight sampled locations are not significantly different.
- H2_o: TKN levels measured at different depth increments are significantly different i.e. measured TKN levels are significantly different with depth.
- H2_a: TKN levels measured at different depth increments are not significantly different i.e. measured TKN levels are not significantly different with depth.

4.1.2.2 <u>Two-Way ANOVA</u>

A Two-Way ANOVA with the response variable as TKN and the two factors of site and depth increment was not able to be applied due to the missing depth increment data at site LS-D2 (8-10 feet) and site LS-D5 (6-8 and 8-10 feet) (Table 26).

4.1.2.3 One-Way ANOVA

A One-Way ANOVA was applied to the TKN data matrix (Table 26). The response variable is TKN and the factors evaluated separately are site and depth increment.

4.1.2.3.1 One-Way ANOVA TKN versus Site

Table 27 provides the One-Way ANOVA results for TKN versus site. Based on the premise that non-overlapping 95% confidence intervals indicate a significant difference, measured sediment/soil TKN levels at 1 of the possible 28 comparisons of sites is significantly different (Table 28).

Table 27. One-way ANOVA results: Total Kjeldahl Nitrogen versus Site

Source	DF	SS	MS	F	P
Site	7	859,049	122,721	2.66	0.029
Error	29	1,335,726	46,060		
Total	36	2,194,775			

Comparison of Sites: Individual 95% CIs For Mean Based on Pooled StDev Site Mean StDev ----+ LS-D1 (-----) 5 213.2 117.0 (-----) LS-D2 4 447.5 424.0 5 228.6 LS-D3 214.2 5 196.8 271.5 LS-D4 LS-D5 3 125.0 54.1 LS-D6 532.2 194.4 (---LS-D7 5 86.2 32.5 (-----) LS-D8 414.6 138.2 (----- * ----) ----+ Pooled StDev = 214.6 0 250 500 750

Table 28. Comparison of measured sediment/soil Total Kjeldahl Nitrogen levels at the eight sampled sites for significant differences.

	LS-D1	LS-D2	LS-D3	LS-D4	LS-D5	LS-D6	LS-D7
LS-D2	No						
LS-D3	No	No					
LS-D4	No	No	No				
LS-D5	No	No	No	No			
LS-D6	No	No	No	No	No		
LS-D7	No	No	No	No	No	Yes	
LS-D8	No						

Note: No and Yes indicate the presence of a significant difference based on non-overlapping 95% confidence intervals.

4.1.2.3.2 One-Way ANOVA TKN versus Depth Increment

Table 29 provides the One-Way ANOVA results for TKN versus depth increment. Based on the premise that non-overlapping 95% confidence intervals indicate a significant difference, measured sediment/soil TKN levels at none of the possible 10 comparisons of depth increments are significantly different; however, the difference between depth increment 0-2 and 2-4 is nearly significantly different (Table 30).

Table 29. One-way ANOVA results: Total Kjeldahl versus Depth Increment.

Source	DF	SS	MS	F	P
Site	4	528,248	132,062	2.54	0.059
Error	32	1,666,527	52,079		
Total	36	2,194,775			

Comparison of Depth Increments:




Table 30. Comparison of measured sediment/soil Total Kjeldahl Nitrogen levels at the five sampled depth increments for significant differences.

	0 – 2 ft	2 – 4 ft	4 -6 ft	6 – 8 ft
2 – 4 ft	No*			
4 – 6 ft	No	No		
6 – 8 ft	No	No	No	
8 – 10 ft	No	No	No	No

Note: No and Yes indicate the presence of a significant difference based on non-overlapping inter-quartile ranges and 95% confidence intervals. (Note * is nearly significantly different)

4.1.3 Nitrate-Nitrite Nitrogen

A data matrix of the measured sediment/soil nitrate-nitrite nitrogen levels in the 37 samples collected among the eight sampling sites and five depth increments is provided in Table 31. Indicative of the "soluble" nature of nitrate-nitrite nitrogen, a majority of the collected samples contained non-detectable levels of nitrate-nitrite nitrogen. Nitrate-nitrite nitrogen is readily taken up by plant growth or leached through the soil profile with water percolation. Figure 26 provides a boxplot of the measured sediment/soil nitrate-nitrite nitrogen levels by sampling sites, and Figure 27 provides a boxplot of the measured sediment/soil nitrate-nitrite levels by depth increment. Boxplots were constructed using the MINITAB statistical software. Non-detect values were set to ½ the detection limit (i.e. 0.02) to calculate statistics.

Table 31. Data matrix for measured sediment/soil nitrate-nitrite nitrogen levels.

Depth		Site						
Increment (ft)	LS-D1	LS-D2	LS-D3	LS-D4	LS-D5	LS-D6	LS-D7	LS-D8
0 - 2	1.1	2.3	n.d.	n.d.	n.d.	1.5	n.d.	2.6
2 - 4	1.2	n.d.	n.d.	n.d.	n.d.	1.4	n.d.	2.4
4 – 6	1.3	n.d.						
6 – 8	n.d.	n.d.	n.d.	n.d.	*	n.d.	n.d.	n.d.
8 – 10	n.d.	*	n.d.	n.d.	*	n.d.	n.d.	n.d.

^{*} Grid cell not sampled due to bore hole collapse. n.d. = non-detect.




Figure 26. Boxplots of sediment/soil nitrate-nitrite as nitrogen levels measured at the eight sampling sites. [Note: The box represents the middle 50% of the data. The line through the box represents the median. The lines (whiskers) extending from the box represent the upper and lower 25% of the data excluding outliers. Outliers, if present, are represented by asterisks (*). The red point on each plot represents the mean.]




Figure 27. Boxplots of sediment/soil nitrate-nitrite nitrogen levels measured at the eight sampled sites by the composited depth increments. [Note: See Figure 26 for explanation of boxplot. The red dashed line represents the nitrate-nitrite nitrogen depth profile plotted by connecting means of the depth increments.]

4.1.3.1 <u>Do Nitrate-Nitrite Levels Significantly Vary Spatially and with Depth at the Proposed Little Sioux project Area?</u>

The following hypotheses and alternative null hypotheses were tested:

- H₁₀: Nitrate-nitrite nitrogen levels measured at the eight sampled locations are significantly different.
- H1_a: Nitrate-nitrite nitrogen levels measured at the eight sampled locations are not significantly different.
- H2_o: Nitrate-nitrite nitrogen levels measured at different depth increments are significantly different i.e. measured nitrate-nitrite nitrogen levels are significantly different with depth.
- H2_a: Nitrate-nitrite nitrogen levels measured at different depth increments are not significantly different i.e. measured nitrate-nitrite nitrogen levels are not significantly different with depth.

4.1.3.2 <u>Two-Way ANOVA</u>

A Two-Way ANOVA with the response variable as nitrate-nitrite nitrogen and the two factors of site and depth increment was not able to be applied due to the missing depth increment data at site LS-D2 (8-10 feet) and site LS-D5 (6-8 and 8-10 feet) (Table 21).

4.1.3.3 One-Way ANOVA

A One-Way ANOVA was applied to the nitrate-nitrite nitrogen data matrix (Table 31). The response variable is nitrate-nitrite nitrogen and the factors evaluated separately are site and depth increment. Non-detect values were set to ½ the detection limit (i.e. 0.02) to calculate statistics.

4.1.3.3.1 One-Way ANOVA Nitrate-Nitrite Nitrogen versus Site

Table 32 provides the One-Way ANOVA results for nitrate-nitrite nitrogen versus site. Based on the premise that non-overlapping 95% confidence intervals indicate a significant difference, measured sediment/soil nitrate-nitrite nitrogen levels at none of the possible 28 comparisons of sites are significantly different (Table 33).

Table 32. One-way ANOVA results: Nitrate-Nitrite Nitrogen versus Site

Source	DF	SS	MS	F	P
Site	7	5.334	0.762	1.43	0.231
Error	29	15.449	0.533		
Total	36	20.783			

Comparison of Sites:

Individual 95% CIs For Mean Based on Pooled StDev

Site	N	Mean	StDev	'++++-
LS-D1	5	0.7280	0.6502	(*)
LS-D2	4	0.5900	1.1400	()
LS-D3	5	0.0200	0.0000	()
LS-D4	5	0.0200	0.0000	()
LS-D5	3	0.0200	0.0000	()
LS-D6	5	0.5920	0.7840	()
LS-D7	5	0.0200	0.0000	()
LS-D8	5	1.0120	1.3602	(*
				+
Pooled St	Dev =	0.7299		-0.70 0.00 0.70 1.40

Table 33. Comparison of measured sediment/soil nitrate-nitrite nitrogen levels at the eight sampled sites for significant differences.

	LS-D1	LS-D2	LS-D3	LS-D4	LS-D5	LS-D6	LS-D7
LS-D2	No						
LS-D3	No	No					
LS-D4	No	No	No				
LS-D5	No	No	No	No			
LS-D6	No	No	No	No	No		
LS-D7	No	No	No	No	No	No	
LS-D8	No						

Note: No and Yes indicate the presence of a significant difference based on non-overlapping 95% confidence intervals.

4.1.3.3.2 One-Way ANOVA Nitrate-Nitrite Nitrogen versus Depth Increment

Table 34 provides the One-Way ANOVA results for nitrate-nitrite nitrogen versus depth increment. Based on the premise that non-overlapping 95% confidence intervals indicate a significant difference, measured sediment/soil nitrate-nitrite nitrogen levels at none of the possible 10 comparisons of depth increments are significantly different. However, the difference between depth increment 0-2 versus 6-8 and 8-10 is nearly significantly different (Table 35).

Table 34. One-way ANOVA results: Nitrate-Nitrite Nitrogen versus Depth Increment.

Source	DF	SS	MS	F	P
Site	4	5.109	1.277	2.61	0.054
Error	32	15.674	0.490		
Total	36	20.783			

Comparison of Depth Increments:

Individual 95% CIs For Mean Based on Pooled StDev

Depth	N	Mean	StDev	
0-2	8	0.9475	1.0908	(*)
2-4	8	0.6375	0.9189	()
4-6	8	0.1800	0.4525	(*)
6-8	7	0.0200	0.0000	()
8-10	6	0.0200	0.0000	()
Pooled St	Dev =	0.6999		0.00 0.60 1.20

Table 35. Comparison of measured sediment/soil nitrate-nitrite nitrogen levels at the five sampled depth increments for significant differences.

	0-2 ft	2-4 ft	4 -6 ft	6 – 8 ft
2 – 4 ft	No			
4 – 6 ft	No	No		
6 – 8 ft	No*	No	No	
8 – 10 ft	No*	No	No	No

Note: No and Yes indicate the presence of a significant difference based on non-overlapping inter-quartile ranges and 95% confidence intervals. (Note * is nearly significantly different)

4.2 <u>Nutrient Tonnage Associated with Suggested Disposal of Sediment/Soil Proposed for</u> Excavation at the Little Sioux Project Area

The IDNR has suggested the following scenario for disposing of excavated material at the proposed Little Sioux project area:

- Stockpile the upper 3 feet of excavated material on one large, 24-acre "upland" area on the USACE tract.
- Excavate from 3 to 6 feet and side-cast this material in two rows along the proposed chute pilot channel (i.e. one on each side). This material may eventually be eroded into the chute and carried to the Missouri River.
- The remainder of the material to be excavated below 6 feet would be hydraulically dredged and discharged directly to the Missouri River.

The premise is that this scenario could significantly reduce the tonnage of nutrients in the Missouri River and potentially delivered to the Gulf of Mexico. To facilitate evaluating this scenario, the total tonnage of nutrients that would be present in the three layers to be excavated was estimated based on the sediment/soil conditions sampled at the Little Sioux project area.

4.2.1 Estimated Amount of Material to be Excavated at the Little Sioux Project

Table 36 gives the estimated volumes of sediment/soil material to be excavated from the three depth layers based on developed design plans for construction of SWH at the Little Sioux project area.

Table 36. Estimated amount of material to be excavated by depth layers at the proposed Little Sioux project area.

Excavation Depth Layer	Volume of Material to be Excavated
0 – 3 feet	120,000 cubic yards
3 – 6 feet	110,000 cubic yards
> 6 feet	200,000 cubic yards

4.2.2 Estimated Nutrient Conditions of the Three Proposed Depth Excavation Layers

Nutrient conditions for the three proposed sediment/soil depth excavation layers were estimated from the nutrient conditions sampled at the Little Sioux project area. The nutrient conditions for the 0-3 and 3-6 layers were estimated as a weighted average of the appropriate sampled 2-foot depth increments. Table 37 provides the estimated average nutrient conditions for the 0-3, 3-6, and greater than 6 foot depth layers.

Table. 37. Estimated average nutrient conditions of the three proposed depth excavation layers at the Little Sioux project area.

Depth Layer	Total Phosphorus (mg/kg)	Total Kjeldahl Nitrogen (mg/kg)	Nitrate-Nitrite Nitrogen (mg/kg)
0-3 feet	463	402	0.8
3-6 feet	407	220	0.3
> 6 feet	420	227	0.0

4.2.3 Estimation of the Nutrient Tonnage Associated with the Three Proposed Depth Excavation Layers

The estimated average nutrient conditions of the proposed three depth excavation layers (Table 37) were applied to the estimated amount of material to be excavated from the defined three depth layers (Table 36) to estimate the tonnage of nutrients present in the three depth layers. The conversion of sampled alluvial sediment/soil weight to volume is based on the relationship show in Table 38 that is used by the Omaha District. The mean percent sand of the sediment/soil samples collected at the eight sampled sites at the proposed Little Sioux project area ranged from 42.4 to 91.1 percent. Thus, the relationship of 95 lbs/cu-ft was used to estimate the sediment/soil weight for the proposed excavation volumes at the Little Sioux project area. Table 39 gives the estimated tonnage of nutrients present in the defined three depth layers.

Table 38. Relationship used by the Omaha District to estimate the weight of alluvial sediment based on the percent sand present.

Sediment Composition	Estimated Weight of Sediment
< 10% Sand	85 pounds/cubic foot
10 to 50% Sand	90 pounds/cubic foot
> 50% Sand	95 pounds/cubic foot

Table. 39. Estimated nutrient tonnage in the three proposed depth excavation layers at the Little Sioux project area.

Depth Layer	Cubic Yards of Excavated Material	Total Phosphorus (tons)	Total Kjeldahl Nitrogen (tons)	Nitrate-Nitrite Nitrogen (tons)
0-3 feet	120,000	71.3	61.9	0.1
3-6 feet	110,000	57.4	31.0	< 0.1
> 6 feet	200,000	107.7	58.2	< 0.1
TOTAL	430,000	236.4	145.0	< 0.1

4.2.4 Comparison of Estimated Phosphorus Tonnage of Excavated Material to Existing Conditions in the Missouri River and Gulf of Mexico

The National Research Council (NRC) of the National Academies published the report, "Missouri River Planning – Recognizing and Incorporating Sediment Management" which assessed nutrient loadings to the Missouri River and Gulf of Mexico (NRC, 2011). The report concluded that potential nitrogen loading from hydraulic dredging to construct SWH along the Missouri River was likely not a concern, but total phosphorus loadings could be a concern regarding Gulf of Mexico hypoxia. Currently, the total phosphorus load to the Gulf of Mexico is estimated to be 154,300 metric tons per year, with the contribution of the Missouri River to this total load estimated to be between 16.8% and 20% (NRC, 2011). Assuming the proposed SWH construction at the Little Sioux project area would be completed within one year, the comparison of the total phosphorus tonnage in the suggested three depth excavations at the Little Sioux project area to annual total phosphorus loadings in the Missouri River and delivered to the Gulf of Mexico are shown in Table 40. These percentages are upper bound estimates, as sediment deposition processes in the Missouri and Mississippi River channels would reduce loads delivered to the Gulf, and actual downstream deliveries would be significantly less than these values.

Table 40. Estimated total phosphorus loadings from the proposed three depth excavation layers as a percent of the existing Missouri River annual total phosphorus loadings and the annual total phosphorus load delivered to the Gulf of Mexico.

Depth Layer	Total Phosphorus (metric tons)	Percent of Annual Missouri River Total Phosphorus Load*	Percent of Annual Total Phosphorus Load Delivered to the Gulf of Mexico*
0-3 feet	64.6	0.228%	0.042%
3-6 feet	52.1	0.183%	0.034%
> 6 feet	97.7	0.344%	0.063%
TOTAL	214.6	0.755%	0.139%

^{*} These percentages are upper bound estimates, as sediment deposition processes in the Missouri and Mississippi River channels would reduce loads delivered to the Gulf, and actual downstream deliveries would be significantly less than these values.

4.3 <u>Comparison of Total Phosphorus Levels Measured at the Proposed Little Sioux Project Area</u> to Total Phosphorus Levels Present in Off-Site Soils

The amount of phosphorus in soil that is available for plant production (i.e. Soil Test Phosphorus - STP) is commonly measured to identify fertilization needs for agricultural production. STP is typically much lower than the total phosphorus present in the soil and potentially deliverable to streams and rivers through erosion. Recent concerns with the environmental impact of phosphorus have resulted in efforts to determine the amount of total phosphorus present in soils.

4.3.1 Phosphorus in Iowa Soils

Total phosphorus levels expected in Iowa soils are identified by Fenton 1999 (Attachment 4). Biosequence effects on the genesis and resulting differences in soil phosphorus have long been recognized (Fenton, 1999). Total phosphorus in Iowa soils tends to be higher in the surface horizon, decreases to a minimum and then increases with depth within members of the biosequence (Fenton, 1999). The general trend of the distribution is similar whether the parent material is loess or glacial till (Fenton 1999). The total phosphorus depth distributions for various Iowa soil types, as reported by Fenton, 1999, are shown in Figure 26.




Figure 26. Total phosphorus depth distributions for various Iowa soil types, as reported by Fenton, 1999.

4.3.2 Phosphorus in Wisconsin Soils

For nutrient management planning and other issues, the State of Wisconsin has identified the need to know the total phosphorus level present in soils within the state. The state has evaluated procedures to convert STP to total phosphorus. As part of this effort, available total phosphorus levels for soils within the State of Wisconsin were compiled and are shown in Figure 27 (Bundy and Good, 2013).




Figure 27. Total phosphorus found in Wisconsin soils.

4.3.3 Total Phosphorus Levels measured at the Proposed Little Sioux project Site

The total phosphorus levels measured in collected sediment/soil samples at the proposed Little Sioux project area are within the range of expected values based on soils and land use present at the project site. The sediment/soil total phosphorus levels measured at the proposed Little Sioux project area exhibited a similar relationship with depth as indicated for Iowa soils by Fenton, 1999. This relationship of high levels near the surface decreasing with depth and then increasing with greater depth is shown in Figure 23.

5 REFERENCES

- **Bundy L.G. and L.W. Good. 2013.** Soil Test P vs. Total P in Wisconsin Soils. Department of Soil Science, University of Wisconsin-Madison.

 (http://www.soils.wisc.edu/extension/area/2003/Bundy_stp.pdf)
- **Fenton, T.E. 1999.** Phosphorus in Iowa Soils. December 3, 1999. Agronomy Department, Iowa State University.
- National Research Council of the National Academies. 2011. Missouri River Planning Recognizing and Incorporating Sediment Management. Committee on Missouri River Recovery and Associated Sediment Management Issues, Water Science and Technology Board, Division of Earth and Life Studies. The National Academies Press, Washington, D.C.
- **USACE. 2013.** Water Quality Sampling Report and Factual Determinations Results of Sediment Sampling and Elutriate Testing at the Proposed Little Sioux Bend Shallow Water Habitat Project Site. April 2013. Water Quality Unit, Water Control and Water Quality Section, Hydrological Engineering Branch, Engineering Division, Omaha District, U.S. Army Corps of Engineers.

Attachment 1

Sampling and Analysis Plan Addendum

SAMPLING AND ANALYSIS PLAN ADDENDUM

for

2013 Elutriate Sampling – Missouri River Little Sioux Bend Project Area

Project Number: SPS-LSXBND-001

Prepared By:

Water Control and Water Quality Section Hydrologic Engineering Branch U.S. Army Corps of Engineers – Omaha District

September 2013

USACE – Water Quality Unit Sampling Coordinator	Date
USACE – Water Quality Unit Team Leader	Date
USACE – Chief, Water Control and Water Quality Section	Date
USACE – Chief, Sedimentation & Channel Stabilization Section	Date
USACE – (CENWO-PM-AE)	Date

ADDENDUM (5-September-2013)

(This Addendum was prepared to collect additional sediment/soil samples to address recent concerns raised by the State of Iowa regarding the discharge of nutrients to the Missouri River via the proposed dredging discharge. It is meant to supplement the original SAP to address the need for additional information on the level of nutrients in material targeted for excavation.)

1. PROJECT DESRIPTION

1.1 BACKGROUND INFORMATION

1.1.1 Project Location

The project area is located in Harrison County, Iowa and Burt County, Nebraska along the Little Sioux Bend of the Missouri River between river miles (RM) 666 and 669 (Attachment 1).

5. DATA COLLECTION APPROACH

5.1 DATA COLLECTION DESIGN

5.1.1 Sediment/Soil Samples

Additional sediment/soil samples will be collected at eight sites (LS-D1, LS-D2, LS-D3, LS-D4, LS-D5, LS-D6, LS-D7, and LS-D8. The location of the eight sites within the project area is shown in Attachments 1 and 2. Preliminary latitude and longitude coordinates for the eight sites are given in Table 1. The "actual" location of the sampled sites will be determined with a GPS unit in the field when the samples are collected.

Table 1. Preliminary latitude and longitude coordinates for the eight locations where sediment/soil samples will be collected for analysis.

Site	Latitude	Longitude
LS-D1	41° 47' 17.8"	96° 04' 00.7"
LS-D2	41° 47' 10.4"	96° 04' 05.5"
LS-D3	41° 47' 04.2"	96° 04' 10.5"
LS-D4	41° 46' 58.7"	96° 04' 17.3"
LS-D5	41° 46' 51.0"	96° 04' 22.2"
LS-D6	41° 46' 43.7"	96° 04' 27.8"
LS-D7	41° 46' 39.2"	96° 04' 31.4"
LS-D8	41° 46' 33.2"	96° 04' 32.7"

Five depth-discrete sediment/soil samples will be collected at each of the eight sites. The five depth discrete sediment/soil samples with consist of a composted sample collected over 2-foot depth intervals from the surface to a depth of 10 feet (i.e. 0-2, 2-4, 4-6, 6-8, and 8-10 feet).

5.2 MEASUREMENT AND SAMPLING METHODS

5.2.2 Sediment/Soil Samples

Sediment/soil samples will be collected at Sites LS-S1, LS-S2, LS-S3, LS-D4, LS-D5, LS-D6, LS-D7, and LS-D8. The equipment, supplies, and procedures to be used to collect the soil samples are as follows.

5.2.2.1 Equipment and Supplies

- 1) Gas powered auger head
- 2) Stainless steel coring device
- 3) Gasoline
- 4) 1-Liter plastic bottles
- 5) Sample bottle labels
- 6) ARF
- 7) Field Sheets
- 8) GPS device
- 9) 5 gallon buckets
- 10) Pick/hammer
- 11) Screwdriver
- 12) Scrub brush

5.2.2.2 Sediment/Soil Collection Procedure

- 1) Select sample site and record general information (including Latitude/Longitude) on the field sheet.
- 2) Remove any vegetation near the proposed boring side (2-3 foot diameter circle).
- Set out equipment near the boring site.
- 4) Attach the corer to the auger head, bore down and collect sample in approximately one-foot increments.
- 5) After each coring, detach suspend the corer over a 5-gallon plastic bucket and deposit the sample into the bucket.
- 6) Heavy clays may require a screwdriver, hammer and/or wooden stake or other tool to remove the sample from the corer.
- 7) When appropriate cores have been collected in the bucket, homogenize the contents and transfer a subsample to a 1-Liter plastic bottle. Affix completed sample label to the bottle.
- 8) Clean the coring device, tools and sample collection bucket between sample locations.
- 9) Deliver the samples and an analytical request form to the laboratory analyzing the samples.

5.4 PARAMETERS TO BE MEASURED

The following parameters that will be analyzed in the laboratory from the collected sediment/soil samples:

- 1) Particle Size
- 2) Nitrogen, Total Kjeldahl
- 3) Nitrogen, Nitrate-Nitrite as N
- 4) Phosphorus, Total

5.5 LABORATORY ANALYTICAL METHODS AND COSTS

Table 2 provides methods, detection limits, and costs for parameters to be analyzed on collected soil samples.

Table. 2. Parameters to be Analyzed on Collected Sediment/Soil Samples and Unit Costs.

Parameter	Method	Detection Limit	Analytical Cost
PHYSICAL AND AGGREGATE PROPERTIES			
Particle Size	Sieve (Minimum Sieve #200)	0.001 mm	\$60.00
NUTRIENTS			
Nitrogen, Kjeldahl Total as N	EPA 351.3	0.2 mg/kg	27.50
Nitrogen, Nitrate/Nitrite Total as N	EPA 353.2	0.02 mg/kg	13.00
Phosphorus, Total	SM4500PF	0.02 mg/kg	27.00
Tota	\$127.50		

7. PROJECTED COSTS FOR FIELD COLLECTION AND LABORATORY ANALYSIS OF ELUTRIATE SAMPLES

Field Collection:


Preparation and collection of required samples 40 man hours @ \$100 = \$4,000

Laboratory Analysis (Midwest Laboratories):


Analyzed Media	Number of Samples	Unit Cost per Sample	Total Cost
Sediment/Soil	40	\$127.50	\$5,100

Total Costs = \$4,000.00 (Field Collection) + \$5,100 (Lab Analysis) = \$9,100

ATTACHMENT 1. Little Sioux Bend Project Alignment and Additional Sediment/Soil Sampling Sites.



ATTACHMENT 2. Little Sioux Bend Project Sampling Sites (Imagery Date 18-Jul-2012).



ATTACHMENT 3. Field Sheet for Little Sioux Additional Sediment/Soil Sampling.

(U.S. Army Corps of Engineers - Omaha District - Water Quality Unit)

FIELD DATA SHEET

Project Name: Little Sioux Additional Sediment/Soil Sampling	Project Number:	SPS-LSXBND-001
Date:		
Site Location: Little Sioux SWH Project, Missouri River		
Site Numbers: LS-D1, LS-D2, LS-D3, LS-D4, LS-D5, LS-D6,	S-D7, LS-D8	
Collectors:		

	GPS MEASUREMENTS	
GPS Device Used:		
Site LS-D1: Latitude:	Longitude:	
Site LS-D2: Latitude:	Longitude:	
Site LS-D3: Latitude:	Longitude:	
Site LS-D4: Latitude:	Longitude:	
Site LS-D5: Latitude:	Longitude:	
Site LS-D6: Latitude:	Longitude:	
Site LS-D7: Latitude:	Longitude:	
Site LS-D8: Latitude:	Longitude:	

SAMPLES COLLECTED									
	Sample		Samp	led De	pth (ft)		Collection	Sampling	
Sample Type	Location	0-2	2-4	4-6	6-8	8-10	Time	Method	
Sediment/Soil	LS-D1							Composite Core	
Sediment/Soil	LS-D2							Composite Core	
Sediment/Soil	LS-D3							Composite Core	
Sediment/Soil	LS-D4							Composite Core	
Sediment/Soil	LS-D5							Composite Core	
Sediment/Soil	LS-D6							Composite Core	
Sediment/Soil	LS-D7							Composite Core	
Sediment/Soil	LS-D8							Composite Core	

COMMENTS:

Attachment 2

Particle Size Distribution Reports



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com Page 2 of 5


Report Number 13-301-2009

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2009

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195878 Source of Sample: Date: 10/21/13 Location: LS-D1A Elev./Depth:



% COBBLES	% GRAVEL		% GRAVEL % SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.1	7.2	79.9	11.8	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .75 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 99.4 95.5 77.8 15.1 12.8		

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.337 D ₃₀ = 0.183 C _u = 3.97	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.246 \\ \text{D}_{15} = 0.146 \\ \text{C}_{\text{C}} = 2.20 \end{array}$	D ₅₀ = 0.223 D ₁₀ = 0.0619
USCS=	Classification AASHT	-O=
	<u>Remarks</u>	

Figure

^{* (}no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number


Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2010

Client: US ARMY CORPS OF ENGINEERS

13-301-2010



% COBBLES	% GRAVEL		% GRAVEL % SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.5	36.3	58.3	3.9	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .44 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 98.4 87.4 34.9 5.5 4.9		

	Soil Description	!
	Attaubauu Limita	
PL=	Atterberg Limits	PI=
D ₈₅ = 0.574 D ₃₀ = 0.279 C _U = 2.23	$\begin{array}{c} \underline{\text{Coefficients}} \\ D_{60} = 0.409 \\ D_{15} = 0.211 \\ C_{\text{C}} = 1.04 \end{array}$	D ₅₀ = 0.363 D ₁₀ = 0.183
USCS=	Classification AASH	ГО=
	<u>Remarks</u>	

^{* (}no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number


Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2011

Client: US ARMY CORPS OF ENGINEERS

13-301-2011



9/ CORRI EC	% GR	% GRAVEL		% SAND		% FINES	
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.1	13.3	71.5	13.7	1.4

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .44 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 99.5 95.1 69.2 20.2 15.1		

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.407 D ₃₀ = 0.179 C _u = 6.13	$\begin{array}{c} \underline{\text{Coefficients}} \\ D_{60} = 0.264 \\ D_{15} = 0.0742 \\ C_{\text{C}} = 2.81 \end{array}$	D ₅₀ = 0.233 D ₁₀ = 0.0431
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

Figure

^{* (}no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com


Report Number 13-301-2012

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2012

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GR	AVEL	L %SAND)	% FINES	
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	5.0	42.1	48.9	4.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .44 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 99.8 97.9 88.2 66.0 52.9		

0.0		.0	• /	
		Soil Description	<u>on</u>	
PL=		Atterberg Limi LL=	<u>ts</u> Pl=	
D ₈₅ = D ₃₀ = C _u =	0.269 0.0426 5.06	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = \ 0.107 \\ \text{D}_{15} = \ 0.0283 \\ \text{C}_{\text{C}} = \ 0.80 \end{array}$	D ₅₀ = D ₁₀ =	0.0684 0.0212
USC	S=	Classification AASI		
		<u>Remarks</u>		

Figure

⁽no specification provided)




13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number
Page 2 of 5
13-301-2013

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2013

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL			% SAND		% FINES	
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	6.2	61.2	30.5	2.1

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 99.7 97.8 82.0 41.8 32.6		

Atterberg Limits LL=	PI=
Coefficients D ₆₀ = 0.210 D ₁₅ = 0.0439 C _C = 0.63	D ₅₀ = 0.179 D ₁₀ = 0.0348
Classification AASHTO=	=
<u>Remarks</u>	
	$\begin{array}{c} \textbf{Coefficients} \\ \textbf{D}_{60} = 0.210 \\ \textbf{D}_{15} = 0.0439 \\ \textbf{C}_{c} = 0.63 \\ \hline \\ \textbf{Classification} \\ \textbf{AASHTO} = 0.0000000000000000000000000000000000$

^{* (}no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com


Report Number
Page 2 of 5
13-301-2014

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2014

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195883 Source of Sample: Date: 10/21/13 Location: LS-D2A Elev./Depth:



% COBBLES	% GR	% GRAVEL		% SAND		% FINES	
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.3	32.9	55.2	11.6

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .75 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 99.5 80.0 66.8		

0.0	02.7	001	_	11.0
		Soil Description	<u>n</u>	
PL=		Atterberg Limits	<u>s</u> Pl=	
D ₈₅ = D ₃₀ = C _u =	0.185 0.0268 20.60	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.0606 \\ \text{D}_{15} = 0.0114 \\ \text{C}_{\text{C}} = 4.02 \end{array}$	D ₅₀ = D ₁₀ =	0.0468 0.0029
USC	S=	Classification AASH	TO=	
		<u>Remarks</u>		

^{* (}no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com Page 2 of 5


Report Number 13-301-2015

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2015

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195884 Source of Sample: Date: 10/21/13 Location: LS-D2B Elev./Depth:



% COBBLES	% GR	AVEL	% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.1	61.0	36.1	2.8

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.7 47.1 38.9		

	Soil Description	
PL=	Atterberg Limits LL=	Pl=
D ₈₅ = 0.256 D ₃₀ = 0.0542 C _u = 7.16	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.190 \\ \text{D}_{15} = 0.0346 \\ \text{C}_{\text{C}} = 0.59 \end{array}$	D ₅₀ = 0.160 D ₁₀ = 0.0265
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

Figure

⁽no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number 13-301-2016


Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT **Report No.:** 13-301-2016

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195885 Source of Sample: Date: 10/21/13 Location: LS-D2C Elev./Depth:



% COBBLES	% GR	AVEL	% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.2	72.5	25.4	1.9

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. #4 #8 #16 #30 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.5 37.9 27.3		

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.262 D ₃₀ = 0.114 C _u = 7.52	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.204 \\ \text{D}_{15} = 0.0402 \\ \text{C}_{\text{C}} = 2.33 \end{array}$	D ₅₀ = 0.181 D ₁₀ = 0.0272
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

Figure (no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number


Page 2 of 6

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2017

Client: US ARMY CORPS OF ENGINEERS

13-301-2017



% COBBLES	% GR	% GRAVEL % SAND		% FINES			
% COBBLES	CRS.	FINE	CRS.	CRS. MEDIUM FIN		SILT	CLAY
0.0	0.0	0.0	0.0	0.1	88.9	10.0	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.6 22.0 11.0		

	Soil Description	
PL=	Atterberg Limits	PI=
D ₈₅ = 0.270 D ₃₀ = 0.167 C _u = 3.22	Coefficients D60= 0.223 D15= 0.100 Cc= 1.82	D ₅₀ = 0.205 D ₁₀ = 0.0692
USCS=	Classification AASH1	
	<u>Remarks</u>	

^{* (}no specification provided) Figure



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number
Page 3 of 6
13-301-2017


Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2017

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195886 DUP Source of Sample: Date: 10/21/13

Location: LS-D2D DUP Elev./Depth:



% COBBLES	% GR	AVEL		% SAND		% FINES	
% COBBLES	CRS.	FINE	CRS.	CRS. MEDIUM FINE		SILT	CLAY
0.0	0.0	0.0	0.0	0.2	89.0	9.8	1.0

SIEVE PERCENT SPEC.* PASS? 3 in. 100.0 (X=NO) 1.5 in. 100.0 (X=NO) .375 in. 100.0 (X=NO) #4 100.0 (X=NO) #8 100.0 (X=NO) #16 100.0 (X=NO) #10 100.0 (X=NO) #10 100.0 (X=NO) #10 100.0 (X=NO) #2 100.0 (X=NO)				
3 in. 100.0 1.5 in. 100.0 .75 in. 100.0 .375 in. 100.0 #4 100.0 #8 100.0 #16 100.0 #30 100.0 #50 99.5 #100 21.8	SIEVE	PERCENT	SPEC.*	PASS?
1.5 in	SIZE	FINER	PERCENT	(X=NO)
	1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.5 21.8		

	Soil Description	
PL=	Atterberg Limits	PI=
D ₈₅ = 0.270 D ₃₀ = 0.168 C _u = 3.17	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.223 \\ \text{D}_{15} = 0.102 \\ \text{C}_{\text{C}} = 1.80 \end{array}$	D ₅₀ = 0.205 D ₁₀ = 0.0702
USCS=	Classification AASHT	
	<u>Remarks</u>	

^{* (}no specification provided) Figure



Report Number 13-301-2018


Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT **Report No.:** 13-301-2018

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195887 Source of Sample: **Date:** 10/21/13 Location: LS-D3A Elev./Depth:



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.1	38.8	53.2	7.9

SIEVE PERCENT SPEC.* PASS? 3 in. 100.0 (X=NO) 1.5 in. 100.0 (X=NO) .75 in. 100.0 (X=NO) .375 in. 100.0 (X=NO) #4 100.0 (X=NO) #16 100.0 (X=NO) #30 100.0 (X=NO) #50 99.8 (X=NO) #100 71.9 (X=NO) #200 61.1 (X=NO)				
3 in. 100.0 1.5 in. 100.0 .75 in. 100.0 .375 in. 100.0 #4 100.0 #8 100.0 #16 100.0 #30 100.0 #50 99.8 #100 71.9	SIEVE	PERCENT	SPEC.*	PASS?
1.5 in. 100.0 .75 in. 100.0 .375 in. 100.0 #4 100.0 #8 100.0 #16 100.0 #30 100.0 #50 99.8 #100 71.9	SIZE	FINER	PERCENT	(X=NO)
	1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.8 71.9		

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.218 D ₃₀ = 0.0300 C _u = 7.51	$\begin{array}{c} \underline{\text{Coefficients}} \\ D_{60} = 0.0714 \\ D_{15} = 0.0131 \\ C_{\text{C}} = 1.33 \end{array}$	D ₅₀ = 0.0516 D ₁₀ = 0.0095
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

Figure (no specification provided)




Report Number 13-301-2019

Page 2 of 2

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2019

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	2.0	86.4	10.6	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .44 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 94.7 22.1 11.6		

2.0	001.	10.0		1.0
	<u>S</u>	oil Description	!	
PL=		<u>terberg Limits</u> _L=	i Pl=	
D ₈₅ = D ₃₀ = C _u =	= 0.278	Coefficients 060= 0.227 015= 0.0965 Cc= 1.88	D ₅₀ = D ₁₀ =	0.207 0.0664
USC		Classification AASHT	ГО=	
		<u>Remarks</u>		

⁽no specification provided)



Report Number 13-301-2020


Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2020

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195889 Source of Sample: Date: 10/21/13 Location: LS-D3C Elev./Depth:



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	1.3	95.1	2.3	1.3

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 96.8 9.1 3.6		

110	70.1	2.0		1.0
	<u>So</u>	oil Description		
PL=		terberg Limits L=	PI=	
D ₈₅ = D ₃₀ = C _u =	= 0.278	Coefficients 060= 0.236 015= 0.162 0= 0.99	D ₅₀ = D ₁₀ =	0.220 0.152
USC		Classification AASHT	O=	
		<u>Remarks</u>		

^{* (}no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number

Page 2 of 5


Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2021

Client: US ARMY CORPS OF ENGINEERS

13-301-2021

Sample No: 2195890 Source of Sample: Date: 10/21/13 Location: LS-D3D Elev./Depth:



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	1.2	95.4	2.1	1.3

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 97.0 9.2 3.4		

	Soil Description	
	Attoukova I imito	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.278 D ₃₀ = 0.188 C _u = 1.55	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.236 \\ \text{D}_{15} = 0.162 \\ \text{C}_{\text{C}} = 0.99 \end{array}$	D ₅₀ = 0.220 D ₁₀ = 0.152
USCS=	Classification AASHT	O=
	Remarks	

⁽no specification provided)




Report Number 13-301-2023

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2023

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL			% SAND		% FINES	
CRS. FINE		CRS.	MEDIUM	FINE	SILT	CLAY	
0.0	0.0	0.0	0.0	1.5	92.4	4.8	1.3

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.7 96.7 14.0 6.1		(****)

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.277 D ₃₀ = 0.182 C _u = 2.10	Coefficients D ₆₀ = 0.232 D ₁₅ = 0.152 C _C = 1.28	D ₅₀ = 0.215 D ₁₀ = 0.111
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

⁽no specification provided)



Report Number 13-301-2024


Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2024

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195892 Source of Sample: Date: 10/21/13 Location: LS-D4A Elev./Depth:



% COBBLES	% GRAVEL			% SAND		% FINES	
CRS. FINE		FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	4.7	50.1	33.7	11.5

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 99.9 99.7 86.7 58.2 45.2		

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.286 D ₃₀ = 0.0457 C _u = 54.43	Coefficients D60= 0.159 D15= 0.0123 C _C = 4.53	D ₅₀ = 0.0984 D ₁₀ = 0.0029
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

^{* (}no specification provided)




13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number
Page 2 of 5
13-301-2025

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2025

Client: US ARMY CORPS OF ENGINEERS



GRAIN SIZE - mm % GRAVEL %SAND % FINES % COBBLES FINE CRS. MEDIUM FINE SILT CRS. CLAY 0.0 88.8 0.0 0.4 0.1 5.4 4.0 1.3

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 99.6 99.5 99.3 98.7 86.5 7.5 5.3		

10

500

100

	Soil Description	
	Atterberg Limits	
PL=	LL=	PI=
D ₈₅ = 0.297 D ₃₀ = 0.195 C _u = 1.59	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.248 \\ \text{D}_{15} = 0.167 \\ \text{C}_{\text{C}} = 0.98 \end{array}$	D ₅₀ = 0.230 D ₁₀ = 0.156
USCS=	Classification AASHT	·O=
	<u>Remarks</u>	

0.01

0.001

^{* (}no specification provided) Figure



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number


Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2026

Client: US ARMY CORPS OF ENGINEERS

13-301-2026



9/ CORRI EC	% COBBLES % GRAVEL CRS. FINE			% SAND		% FINES	
% COBBLES			CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	4.3	92.1	2.6	1.0

SIEVE PERCENT SPEC.* PASS? 3 in. 100.0 (X=NO) 1.5 in. 100.0 (X=NO) .375 in. 100.0 (X=NO) #4 100.0 (X=NO) #8 100.0 (X=NO) #16 100.0 (X=NO) #10 100.0 (X=NO) #10 30.0 (X=NO)				
3 in. 100.0 1.5 in. 100.0 .75 in. 100.0 .375 in. 100.0 #4 100.0 #8 100.0 #16 100.0 #30 99.7 #50 88.9 #100 7.0	SIEVE	PERCENT	SPEC.*	PASS?
1.5 in	SIZE	FINER	PERCENT	(X=NO)
	1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100	100.0 100.0 100.0 100.0 100.0 100.0 99.7 88.9 7.0		

1.5	72.1	2.0		1.0
	<u>Sc</u>	oil Description		
PL=		terberg Limits L=	PI=	
D ₈₅ = D ₃₀ = C _u =	: 0.292 E : 0.194 E 1.56 C	Coefficients 060= 0.245 015= 0.167 015= 0.98	D ₅₀ = D ₁₀ =	0.228 0.157
USCS		classification AASHTO	D=	
		<u>Remarks</u>		

^{* (}no specification provided)




Report Number 13-301-2027

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2027

Client: US ARMY CORPS OF ENGINEERS



e/ CORRI EC	% COBBLES			% SAND		% FINES	
% COBBLES			CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	6.7	89.7	2.2	1.4

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .44 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.3 75.6 10.0 3.6		
1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100	100.0 100.0 100.0 100.0 100.0 100.0 99.3 75.6 10.0		

	Soil Description	
	Atterberg Limits	
PL=	LL=	PI=
	0 111 - 1 1 -	
Dos- 0.346	Coefficients	Dea- 0.230
D ₂₀ = 0.191	$D_{16} = 0.255$ $D_{15} = 0.161$	D ₅₀ = 0.230 D ₁₀ = 0.150
D ₈₅ = 0.346 D ₃₀ = 0.191 C _U = 1.69	D ₆₀ = 0.253 D ₁₅ = 0.161 C _c = 0.96	- 10 ****
	•	
USCS=	Classification AASHT	n_
0000-	70.0111	O-
	<u>Remarks</u>	

^{* (}no specification provided)



13-301-2027


Page 3 of 6

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT **Report No.:** 13-301-2027

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195895 DUP Source of Sample: Date: 10/21/13 Location: LS-D4D DUP Elev./Depth:



% COBBLES	% GRAVEL % SAND)	% FINES				
	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY	
	0.0	0.0	0.0	0.0	9.4	87.6	1.6	1.4

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.2 71.6 8.4 3.0		
		I	

	Soil Description	
PL=	Atterberg Limits	PI=
D ₈₅ = 0.371 D ₃₀ = 0.196 C _u = 1.71	$\begin{array}{c} \underline{\text{Coefficients}} \\ D_{60} = 0.263 \\ D_{15} = 0.165 \\ C_{\text{C}} = 0.95 \end{array}$	D ₅₀ = 0.238 D ₁₀ = 0.154
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

Figure (no specification provided)




Report Number 13-301-2028

Page 2 of 2

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2028

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL % SAND)	% FINES			
	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	4.6	87.9	6.5	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.5 79.1 14.4 7.5		

	07.0	0.0		1.0
	<u>So</u>	il Description	ļ	
PL=		<u>erberg Limits</u> L=	Pl=	
D ₈₅ = D ₃₀ = C _u =	= 0.327 D = 0.183 D	Coefficients 60= 0.244 15= 0.151 c= 1.40	D ₅₀ = D ₁₀ =	0.222 0.0979
USC		lassification AASHT	TO=	
		<u>Remarks</u>		

⁽no specification provided)




Report Number 13-301-2029

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2029

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GR	GRAVEL %SAND		% FINES			
	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	4.5	76.3	15.5	3.7

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in.	100.0		
1.5 in.	100.0		
.75 in.	100.0		
.375 in.	100.0		
#4	100.0		
#8	100.0		
#16	99.8		
#30	98.8		
#50	90.1		
#100	29.9		
#200	19.2		

	Soil Description	
PL=	Atterberg Limits LL=	Pl=
D ₈₅ = 0.285 D ₃₀ = 0.150 C _u = 15.12	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.223 \\ \text{D}_{15} = 0.0471 \\ \text{C}_{\text{C}} = 6.89 \end{array}$	D ₅₀ = 0.200 D ₁₀ = 0.0147
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

⁽no specification provided)




Report Number 13-301-2030

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2030

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GR	AVEL	% SAND		% FINES		
	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.6	12.9	83.4	2.1	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 99.5 98.5 94.0 67.8 7.7 3.1		

	Soil Description	
PL=	Atterberg Limits LL=	Pl=
D ₈₅ = 0.408 D ₃₀ = 0.200 C _u = 1.75	$\begin{array}{c} \underline{\text{Coefficients}} \\ D_{60} = 0.273 \\ D_{15} = 0.168 \\ C_{c} = 0.94 \end{array}$	D ₅₀ = 0.245 D ₁₀ = 0.156
USCS=	Classification AASHT	O=
	Remarks	

^{* (}no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number


Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2031

Client: US ARMY CORPS OF ENGINEERS

13-301-2031



% COBBLES	% GR	AVEL		% SANI)	% FINES	
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	5.7	90.6	2.7	1.0

Γ	SIEVE	PERCENT	SPEC.*	PASS?
L	SIZE	FINER	PERCENT	(X=NO)
	3 in. 1.5 in. .75 in. .375 in. .44 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 99.4 97.3 77.8 8.6 3.7		

	Soil Description	
	Atterberg Limits	
PL=	LL=	PI=
D ₈₅ = 0.333 D ₃₀ = 0.191 C _U = 1.63	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.249 \\ \text{D}_{15} = 0.164 \\ \text{C}_{\text{C}} = 0.95 \end{array}$	D ₅₀ = 0.228 D ₁₀ = 0.153
USCS=	Classification AASHT	O=
	Remarks	

^{* (}no specification provided) Figure




Report Number 13-301-2032

rage z or .

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2032

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	3.0	64.1	23.8	9.1

PERCENT	SPEC.*	PASS?
FINER	PERCENT	(X=NO)
100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.6 92.6 39.6 32.9		
	FINER 100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.6 92.6 39.6	FINER PERCENT 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.6 92.6 39.6

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.276 D ₃₀ = 0.0620 C _u = 32.08	Coefficients D ₆₀ = 0.208 D ₁₅ = 0.0119 C _C = 2.86	D ₅₀ = 0.182 D ₁₀ = 0.0065
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

^{* (}no specification provided)




Report Number 13-301-2033

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2033

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GR	AVEL		% SANI)	% FINES	
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.9	75.7	19.2	4.2

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 97.9 44.2 23.4		

	Soil Description	
PL=	Atterberg Limits LL=	Pl=
D ₈₅ = 0.259 D ₃₀ = 0.103 C _U = 6.30	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.191 \\ \text{D}_{15} = 0.0482 \\ \text{C}_{\text{C}} = 1.81 \end{array}$	D ₅₀ = 0.166 D ₁₀ = 0.0304
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

⁽no specification provided)




Report Number 13-301-2034

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2034

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.8	24.7	57.1	17.4

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in75 in375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 98.1 82.5 74.5	PERCENT	(X=NO)

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.173 D ₃₀ = 0.0155 C _U = 18.82	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.0416 \\ \text{D}_{15} = 0.0040 \\ \text{C}_{\text{C}} = 2.60 \end{array}$	D ₅₀ = 0.0312 D ₁₀ = 0.0022
USCS=	Classification AASHT	-O=
	<u>Remarks</u>	

^{* (}no specification provided)




Report Number 13-301-2035

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2035

Client: US ARMY CORPS OF ENGINEERS



% COBBLES % GRAVEL		AVEL	% SAND			% FINES	
% COBBLES	CRS. FINE		CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	2.1	47.9	41.4	8.6

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in.	100.0 100.0		
.75 in. .375 in. #4	100.0 100.0 100.0		
#8 #16	100.0 100.0 99.9		
#30 #50	99.4 95.4		
#100 #200	64.6 50.0		

	Soil Description	
	Attarbara Limita	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.243 D ₃₀ = 0.0347 C _U = 15.74	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.126 \\ \text{D}_{15} = 0.0140 \\ \text{C}_{\text{C}} = 1.19 \end{array}$	D ₅₀ = 0.0750 D ₁₀ = 0.0080
USCS=	Classification AASHT	-O=
	<u>Remarks</u>	

^{* (}no specification provided)




Report Number 13-301-2036

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2036

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195904 Source of Sample: Date: 10/21/13 Location: LS-D6E Elev./Depth:



% COBBLES % GRAVEL CRS. FINE		% SAND			% FINES		
		FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	3.4	58.2	30.7	7.7

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 99.9 99.0 92.8 55.2 38.4		
I	ı	I	ı

<u> </u>		
	Soil Description	1
PL=	Atterberg Limits	<u>\$</u> Pl=
D ₈₅ = 0.264 D ₃₀ = 0.051 C _U = 18.75	$\begin{array}{ccc} & & \underline{\text{Coefficients}} \\ 14 & & D_{60} = 0.168 \\ 16 & & D_{15} = 0.0186 \\ & & C_{\text{C}} = 1.77 \end{array}$	D ₅₀ = 0.129 D ₁₀ = 0.0090
USCS=	Classification AASH	ГО=
	<u>Remarks</u>	

^{* (}no specification provided)



Report Number 13-301-2036


Page 3 of 6

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2036

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195904 DUP Source of Sample: Date: 10/21/13 Location: LS-D6E DUP Elev./Depth:



% COBBLES	% GR	AVEL	VEL %SAND)	% FINES	
%COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	3.2	57.8	31.3	7.7

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 99.9 99.1 93.2 53.7 39.0		

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.264 D ₃₀ = 0.0469 C _u = 19.28	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.173 \\ \text{D}_{15} = 0.0190 \\ \text{C}_{\text{C}} = 1.42 \end{array}$	D ₅₀ = 0.135 D ₁₀ = 0.0090
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

⁽no specification provided)



13611 B Street • Omaha, Nebraska 68144-3693 • (402) 334-7770 • FAX (402) 334-9121 • www.midwestlabs.com

Report Number

Page 2 of 5


Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2037

Client: US ARMY CORPS OF ENGINEERS

13-301-2037

Sample No: 2195905 Source of Sample: Date: 10/16/13 Location: LS-D7A Elev./Depth:



% COBBLES % GRAVEL		AVEL	% SAND			% FINES	
% COBBLES	CRS. FINE		CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.4	68.3	27.7	3.6

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in.	100.0 100.0		
.75 in.	100.0		
.375 in. #4	100.0 100.0		
#8 #16	100.0 100.0		
#30	100.0		
#50 #100	99.0 44.5		
#200	31.3		

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.258 D ₃₀ = 0.0674 C _U = 10.43	Coefficients D ₆₀ = 0.192 D ₁₅ = 0.0280 C _c = 1.28	D ₅₀ = 0.166 D ₁₀ = 0.0185
USCS=	Classification AASHT	-O=
	<u>Remarks</u>	

^{* (}no specification provided) Figure




Report Number 13-301-2038

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2038

Client: US ARMY CORPS OF ENGINEERS



% COBBLES %		VEL %SAND		% FINES			
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	5.7	84.9	8.4	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.2 86.4 23.4 9.4		

	Soil Description	ı.
PL=	Atterberg Limits	i Pl=
D ₈₅ = 0.296 D ₃₀ = 0.166 C _U = 2.73	Coefficients D ₆₀ = 0.233 D ₁₅ = 0.122 C _C = 1.39	D ₅₀ = 0.210 D ₁₀ = 0.0853
USCS=	Classification AASH	ГО=
	<u>Remarks</u>	

^{* (}no specification provided)




Report Number 13-301-2039

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2039

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.3	27.0	69.2	2.5	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. #4 #8 #16 #30	100.0 100.0 100.0 100.0 100.0 99.9 99.2 90.7		
#50 #100 #200	48.1 7.4 3.5		

	Soil Description	
PL=	Atterberg Limits	PI=
D ₈₅ = 0.526 D ₃₀ = 0.233 C _u = 2.19	$\begin{array}{c} \underline{\text{Coefficients}} \\ D_{60} = 0.353 \\ D_{15} = 0.181 \\ C_{\text{C}} = 0.95 \end{array}$	D ₅₀ = 0.308 D ₁₀ = 0.162
USCS=	Classification AASHT	TO=
	<u>Remarks</u>	

⁽no specification provided)




Report Number 13-301-2040

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2040

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GR	GRAVEL % SAND)	% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.7	24.7	70.4	3.2	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 99.6 98.0 89.4 52.7 8.3 4.2		

	Soil Description	
PI =	Atterberg Limits	Pl=
		1 1=
D ₈₅ = 0.529 D ₃₀ = 0.220 C _u = 2.13	Coefficients D ₆₀ = 0.333 D ₁₅ = 0.174 C _C = 0.93	D ₅₀ = 0.289 D ₁₀ = 0.157
USCS=	Classification AASHT	
	<u>Remarks</u>	

^{* (}no specification provided)




Report Number 13-301-2041

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2041

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195909 Source of Sample: Date: 10/16/13 Location: LS-D7E Elev./Depth:



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.3	18.4	75.7	4.6	1.0

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. #4 #8 #16 #30 #50 #100	100.0 100.0 100.0 100.0 100.0 100.0 99.9 99.3 93.9 60.0 10.8		(KEIIG)
#200	5.6		

	Soil Description	
PL=	Atterberg Limits	PI=
D ₈₅ = 0.460 D ₃₀ = 0.205 C _u = 2.20	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.300 \\ \text{D}_{15} = 0.164 \\ \text{C}_{\text{C}} = 1.03 \end{array}$	D ₅₀ = 0.264 D ₁₀ = 0.137
USCS=	Classification AASHT	-O=
	<u>Remarks</u>	

^{* (}no specification provided)




Report Number 13-301-2042

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2042

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL		% SAND			% FINES	
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.2	57.1	33.9	8.8

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in.	100.0		
1.5 in.	100.0		
.75 in.	100.0		
.375 in.	100.0		
#4	100.0		
#8	100.0		
#16	100.0		
#30	99.9		
#50	99.7		
#100	60.8		
#200	42.7		

	Soil Description	
PL=	Atterberg Limits	PI=
D ₈₅ = 0.238 D ₃₀ = 0.0423 C _U = 23.37	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.147 \\ \text{D}_{15} = 0.0154 \\ \text{C}_{\text{C}} = 1.94 \end{array}$	D ₅₀ = 0.106 D ₁₀ = 0.0063
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

⁽no specification provided)




Report Number 13-301-2043

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2043

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL		% SAND			% FINES	
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.0	23.1	64.7	12.2

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in.	100.0		
1.5 in.	100.0		
.75 in.	100.0		
.375 in.	100.0		
#4	100.0		
#8	100.0		
#16	100.0		
#30	100.0		
#50	99.9		
#100	86.0		
#200	76.9		

		-		
	2	Soil Description	<u>on</u>	
PL=	<u> </u>	Atterberg Limi LL=	i <u>ts</u> Pl=	
D ₈₅ = D ₃₀ = C _u =	: 0.140 : 0.0185 12.89	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = 0.0405 \\ \text{D}_{15} = 0.0076 \\ \text{C}_{\text{C}} = 2.69 \end{array}$	D ₅₀ = D ₁₀ =	0.0316
USC	S=	Classification AAS	<u>n</u> HTO=	
		Remarks		

⁽no specification provided)




Report Number 13-301-2044

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2044

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GRAVEL		% SAND		% FINES		
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.0	53.1	41.1	5.8

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .375 in. #4 #8 #16 #30 #50 #100	100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 46.9	LIIOLIII	(X-110)

	Soil Description	
PL=	Atterberg Limits	PI=
D ₈₅ = 0.217 D ₃₀ = 0.0487 C _u = 8.86	$\begin{array}{c} \underline{\text{Coefficients}} \\ \text{D}_{60} = \ 0.112 \\ \text{D}_{15} = \ 0.0260 \\ \text{C}_{\text{C}} = \ 1.68 \end{array}$	D ₅₀ = 0.0819 D ₁₀ = 0.0126
USCS=	Classification AASHTO)=
	<u>Remarks</u>	

⁽no specification provided)




Report Number 13-301-2045

Page 2 of 5

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2045

Client: US ARMY CORPS OF ENGINEERS



% COBBLES	% GR	% GRAVEL		% SANI)	% FINES	
%COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY
0.0	0.0	0.0	0.0	0.0	27.0	63.5	9.5

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. .44 #8 #16 #30 #50 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 87.5 73.0		

0.0	27.0	00.0		,
	<u>s</u>	oil Description	1	
PL=	<u>A</u>	<u>tterberg Limits</u> LL=	<u>s</u> Pl=	
D ₈₅ = D ₃₀ = C _u =	: 0.124 : 0.0316 9.71	Coefficients D ₆₀ = 0.0582 D ₁₅ = 0.0150 C _c = 2.87	D ₅₀ = D ₁₀ =	0.0491 0.0060
USC		Classification AASH	TO=	
		<u>Remarks</u>		

^{* (}no specification provided)



Report Number 13-301-2046


J

Particle Size Distribution Report

Project: LITTLE SIOUX SWH SEDIMENT Report No.: 13-301-2046

Client: US ARMY CORPS OF ENGINEERS

Sample No: 2195914 Source of Sample: Date: 10/16/13 Location: LS-D8E Elev./Depth:



% COBBLES	% GR	AVEL		% SANI)	% FINES			
% COBBLES	CRS.	FINE	CRS.	MEDIUM	FINE	SILT	CLAY		
0.0	0.0	0.0	0.0	0.0	51.9	44.2	3.9		

SIEVE	PERCENT	SPEC.*	PASS?
SIZE	FINER	PERCENT	(X=NO)
3 in. 1.5 in. .75 in. .375 in. #4 #8 #16 #30 #100 #200	100.0 100.0 100.0 100.0 100.0 100.0 100.0 100.0 99.9 67.5 48.1		

	Soil Description	
PL=	Atterberg Limits LL=	PI=
D ₈₅ = 0.226 D ₃₀ = 0.0514 C _u = 6.58	$\begin{array}{c} \underline{\text{Coefficients}} \\ D_{60} = 0.113 \\ D_{15} = 0.0333 \\ C_{\text{C}} = 1.35 \end{array}$	D ₅₀ = 0.0789 D ₁₀ = 0.0173
USCS=	Classification AASHT	O=
	<u>Remarks</u>	

⁽no specification provided)

Attachment 3

Laboratory Analytical Results

Station	Date	Time	Depth	SampleSource	Analyte	Result	Units	Method	DF	MDL	MRL	AnalysisDate	LabNumber
LS-D1A	10/21/2013	14:30	0-2	Composite	Nitrate/Nitrite Nitrogen	1.1	mg/kg dry	EPA 353.2	5	0.04	1.1	28-Oct-13	1300897-01
LS-D1A	10/21/2013	14:30	0-2	Composite	Percent Solids		%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-01
LS-D1A	10/21/2013	14:30	0-2	Composite	Phosphorus (Total)		mg/kg dry	EPA 6010B	51.65	0.9	5.6	23-Oct-13	1300897-01
LS-D1A	10/21/2013	14:30	0-2	Composite	Total Kjeldahl Nitrogen	205	mg/kg dry	PAI-DK 01	5	1.5	26.9	24-Oct-13	1300897-01
LS-D1B	10/21/2013	14:30	2-4	Composite	Nitrate/Nitrite Nitrogen		mg/kg dry	EPA 353.2	5	0.04	1	28-Oct-13	1300897-02
LS-D1B	10/21/2013	14:30	2-4	Composite	Percent Solids	95.68	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-02
LS-D1B	10/21/2013	14:30	2-4	Composite	Phosphorus (Total)	294.6	mg/kg dry	EPA 6010B	46.73	0.8	4.9	23-Oct-13	1300897-02
LS-D1B	10/21/2013	14:30	2-4	Composite	Total Kjeldahl Nitrogen		,	PAI-DK 01	5	1.4	26.1	24-Oct-13	1300897-02
LS-D1C	10/21/2013	14:30	4-6	Composite	Nitrate/Nitrite Nitrogen			EPA 353.2	5	0.04	1.2		1300897-03
LS-D1C	10/21/2013	14:30	4-6	Composite	Percent Solids	82.16		SM 2540 G	1	0.01	0.01		1300897-03
LS-D1C	10/21/2013	14:30	4-6	Composite	Phosphorus (Total)			EPA 6010B	47.26	1	5.8		1300897-03
LS-D1C	10/21/2013	14:30	4-6	Composite	Total Kjeldahl Nitrogen			PAI-DK 01	5	1.7	30.4		1300897-03
LS-D1D	10/21/2013	14:30	6-8	Composite	Nitrate/Nitrite Nitrogen	<0.05	9.9.7	EPA 353.2	5	0.05	1.3		1300897-04
LS-D1D	10/21/2013	14:30	6-8	Composite	Percent Solids	75.61		SM 2540 G	1	0.01	0.01		1300897-04
LS-D1D	10/21/2013	14:30	6-8	Composite	Phosphorus (Total)			EPA 6010B	49.53	1.1	6.6		1300897-04
LS-D1D	10/21/2013	14:30	6-8	Composite	Total Kjeldahl Nitrogen			PAI-DK 01	5	1.8	33.1		1300897-04
LS-D1E	10/21/2013	14:30	8-10	Composite	Nitrate/Nitrite Nitrogen	<0.05	0	EPA 353.2	5	0.05	1.3		1300897-05
LS-D1E	10/21/2013	14:30	8-10	Composite	Percent Solids	75.65		SM 2540 G	1	0.01	0.01		1300897-05
LS-D1E	10/21/2013	14:30	8-10	Composite	Phosphorus (Total)			EPA 6010B	44.19	1	5.8		1300897-05
LS-D1E	10/21/2013	14:30	8-10	Composite	Total Kjeldahl Nitrogen		,	PAI-DK 01	5	1.8	33		1300897-05
LS-D2A	10/21/2013	13:10	0-2	Composite	Nitrate/Nitrite Nitrogen		mg/kg dry	EPA 353.2	5	0.04	1.2		1300897-06
LS-D2A	10/21/2013	13:10	0-2	Composite	Percent Solids	82.75		SM 2540 G	1	0.01	0.01		1300897-06
LS-D2A	10/21/2013	13:10	0-2	Composite	Phosphorus (Total)			EPA 6010B	47.73	1	5.8		1300897-06
LS-D2A	10/21/2013	13:10	0-2	Composite	Total Kjeldahl Nitrogen			PAI-DK 01	5	1.6	30.2		1300897-06
LS-D2B	10/21/2013	13:10	2-4	Composite	Nitrate/Nitrite Nitrogen	<0.04		EPA 353.2	5	0.04	1.2		1300897-07
LS-D2B	10/21/2013	13:10	2-4	Composite	Percent Solids	83.08		SM 2540 G	1	0.01	0.01		1300897-07
LS-D2B	10/21/2013	13:10	2-4	Composite	Phosphorus (Total)			EPA 6010B	47.66	1	5.7		1300897-07
LS-D2B	10/21/2013	13:10	2-4	Composite	Total Kjeldahl Nitrogen			PAI-DK 01	5	1.6	30.1		1300897-07
LS-D2C	10/21/2013	13:10	4-6	Composite	Nitrate/Nitrite Nitrogen	<0.05		EPA 353.2	5	0.05	1.4		1300897-08
LS-D2C	10/21/2013	13:10	4-6	Composite	Percent Solids	73.95		SM 2540 G	1 77	0.01	0.01		1300897-08
LS-D2C	10/21/2013	13:10	4-6	Composite	Phosphorus (Total)			EPA 6010B	47.73	1.1	6.5		1300897-08
LS-D2C	10/21/2013	13:10	4-6	Composite	Total Kjeldahl Nitrogen			PAI-DK 01	5 5	1.8	33.8		1300897-08
LS-D2D	10/21/2013	13:10	6-8	Composite	Nitrate/Nitrite Nitrogen	<0.05		EPA 353.2	5	0.05	1.4		1300897-09
LS-D2D LS-D2D	10/21/2013	13:10 13:10	6-8 6-8	Composite	Percent Solids Phosphorus (Total)	73.76		SM 2540 G EPA 6010B	45.00	0.01	0.01		1300897-09 1300897-09
LS-D2D LS-D2D	10/21/2013 10/21/2013	13:10	6-8	Composite Composite	Total Kjeldahl Nitrogen			PAI-DK 01	45.02 5	1.9	6.1 33.9		1300897-09
									_				
LS-D3A LS-D3A	10/21/2013	12:30	0-2	Composite	Nitrate/Nitrite Nitrogen	<0.04		EPA 353.2	5 1	0.04	1.1		1300897-10
LS-D3A LS-D3A	10/21/2013	12:30	0-2	Composite	Percent Solids	87.57		SM 2540 G		0.01	0.01		1300897-10
	10/21/2013	12:30	0-2	Composite	Phosphorus (Total)			EPA 6010B	50.45	1	5.8 28.5		1300897-10
LS-D3A LS-D3B	10/21/2013	12:30 12:30	0-2 2-4	Composite	Total Kjeldahl Nitrogen	< 0.04	,	PAI-DK 01	5 5	1.6 0.04	∠8.5 1		1300897-10
	10/21/2013		2-4	Composite	Nitrate/Nitrite Nitrogen		mg/kg dry %	EPA 353.2	5	0.04			1300897-11
LS-D3B LS-D3B	10/21/2013 10/21/2013	12:30 12:30	2-4	Composite	Percent Solids			SM 2540 G EPA 6010B	48.88	0.01	0.01 5.1		1300897-11 1300897-11
LS-D3B LS-D3B	10/21/2013	12:30	2-4	Composite	Phosphorus (Total)			PAI-DK 01	48.88	1.4	26.1		1300897-11
LS-D3B LS-D3C	10/21/2013	12:30	2-4 4-6	Composite	Total Kjeldahl Nitrogen	< 0.04		EPA 353.2	5	0.04	26.1		1300897-11
LS-D3C	10/21/2013	12:30	4-6 4-6	Composite	Nitrate/Nitrite Nitrogen Percent Solids	97.73		SM 2540 G	5	0.04	0.01		1300897-12
F9-D3C	10/21/2013	12:30	4-0	Composite	reicent Solias	91.73	70	SIVI 2540 G	1	บ.บา	0.01	25-001-13	1300897-12

Station	Date	Time	Depth	SampleSource	Analyte	Result	Units	Method	DF	MDL	MRL	AnalysisDate	LabNumber
LS-D3C	10/21/2013	12:30	4-6	Composite	Phosphorus (Total)	343.4	mg/kg dry	EPA 6010B	49.38	0.9	5.1	24-Oct-13	1300897-12
LS-D3C	10/21/2013	12:30	4-6	Composite	Total Kjeldahl Nitrogen	67.6	mg/kg dry	PAI-DK 01	5	1.4	25.6	24-Oct-13	1300897-12
LS-D3D	10/21/2013	12:30	6-8	Composite	Nitrate/Nitrite Nitrogen	< 0.04	mg/kg dry	EPA 353.2	5	0.04	1	28-Oct-13	1300897-13
LS-D3D	10/21/2013	12:30	6-8	Composite	Percent Solids	97.14	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-13
LS-D3D	10/21/2013	12:30	6-8	Composite	Phosphorus (Total)	332.4	mg/kg dry	EPA 6010B	51.95	0.9	5.3	24-Oct-13	1300897-13
LS-D3D	10/21/2013	12:30	6-8	Composite	Total Kjeldahl Nitrogen	74	mg/kg dry	PAI-DK 01	5	1.4	25.7	24-Oct-13	1300897-13
LS-D3E	10/21/2013	12:30	8-10	Composite	Nitrate/Nitrite Nitrogen	<0.04		EPA 353.2	5	0.04	1.1	28-Oct-13	1300897-14
LS-D3E	10/21/2013	12:30	8-10	Composite	Percent Solids	90.59	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-14
LS-D3E	10/21/2013	12:30	8-10	Composite	Phosphorus (Total)	387.9	mg/kg dry	EPA 6010B	48.78	0.9	5.4	24-Oct-13	1300897-14
LS-D3E	10/21/2013	12:30	8-10	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.5	27.6	24-Oct-13	1300897-14
LS-D4A	10/21/2013	11:50	0-2	Composite	Nitrate/Nitrite Nitrogen	< 0.04	mg/kg dry	EPA 353.2	5	0.04	1.1	28-Oct-13	1300897-15
LS-D4A	10/21/2013	11:50	0-2	Composite	Percent Solids	90.87		SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-15
LS-D4A	10/21/2013	11:50	0-2	Composite	Phosphorus (Total)		mg/kg dry	EPA 6010B	52.55	1	5.8		1300897-15
LS-D4A	10/21/2013	11:50	0-2	Composite	Total Kjeldahl Nitrogen	681	mg/kg dry	PAI-DK 01	5	1.5	27.5	24-Oct-13	1300897-15
LS-D4B	10/21/2013	11:50	2-4		Nitrate/Nitrite Nitrogen	<0.04		EPA 353.2	5	0.04	1	28-Oct-13	1300897-16
LS-D4B	10/21/2013	11:50	2-4	Composite	Percent Solids	97.33		SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-16
LS-D4B	10/21/2013	11:50	2-4	Composite	Phosphorus (Total)			EPA 6010B	50.45	0.9	5.2		1300897-16
LS-D4B	10/21/2013	11:50	2-4	Composite	Total Kjeldahl Nitrogen			PAI-DK 01	5	1.4	25.7	25-Oct-13	1300897-16
LS-D4C	10/21/2013	11:50	4-6	Composite	Nitrate/Nitrite Nitrogen	<0.04	mg/kg dry	EPA 353.2	5	0.04	1		1300897-17
LS-D4C	10/21/2013	11:50	4-6	Composite	Percent Solids		%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-17
LS-D4C	10/21/2013	11:50	4-6	Composite	Phosphorus (Total)		mg/kg dry	EPA 6010B	46.58	0.8	4.8	24-Oct-13	1300897-17
LS-D4C	10/21/2013	11:50	4-6	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.4	25.7	25-Oct-13	1300897-17
LS-D4D	10/21/2013	11:50	6-8	Composite	Nitrate/Nitrite Nitrogen	<0.04	mg/kg dry	EPA 353.2	5	0.04	1.1	28-Oct-13	1300897-18
LS-D4D	10/21/2013	11:50	6-8	Composite	Percent Solids	89.97	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-18
LS-D4D	10/21/2013	11:50	6-8	Composite	Phosphorus (Total)	321.7	mg/kg dry	EPA 6010B	44.56	0.8	5	24-Oct-13	1300897-18
LS-D4D	10/21/2013	11:50	6-8	Composite	Total Kjeldahl Nitrogen	64.4	mg/kg dry	PAI-DK 01	5	1.5	27.8	25-Oct-13	1300897-18
LS-D4E	10/21/2013	11:50	8-10	Composite	Nitrate/Nitrite Nitrogen	< 0.05	mg/kg dry	EPA 353.2	5	0.05	1.3	28-Oct-13	1300897-19
LS-D4E	10/21/2013	11:50	8-10	Composite	Percent Solids	76.09		SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-19
LS-D4E	10/21/2013	11:50	8-10	Composite	Phosphorus (Total)	317.6	mg/kg dry	EPA 6010B	47.87	1.1	6.3	24-Oct-13	1300897-19
LS-D4E	10/21/2013	11:50	8-10	Composite	Total Kjeldahl Nitrogen	76.5	mg/kg dry	PAI-DK 01	5	1.8	32.9	25-Oct-13	1300897-19
LS-D5A	10/21/2013	10:20	0-2	Composite	Nitrate/Nitrite Nitrogen	<0.04	mg/kg dry	EPA 353.2	5	0.04	1.2	28-Oct-13	1300897-20
LS-D5A	10/21/2013	10:20	0-2	Composite	Percent Solids	83.04	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-20
LS-D5A	10/21/2013	10:20	0-2	Composite	Phosphorus (Total)	449	mg/kg dry	EPA 6010B	47.64	1	5.7	24-Oct-13	1300897-20
LS-D5A	10/21/2013	10:20	0-2	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.6	30.1	25-Oct-13	1300897-20
LS-D5B	10/21/2013	10:20	2-4	Composite	Nitrate/Nitrite Nitrogen	< 0.04	mg/kg dry	EPA 353.2	5	0.04	1.2	28-Oct-13	1300897-21
LS-D5B	10/21/2013	10:20	2-4	Composite	Percent Solids	80.21		SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-21
LS-D5B	10/21/2013	10:20	2-4	Composite	Phosphorus (Total)	294	mg/kg dry	EPA 6010B	49.95	1.1	6.2	24-Oct-13	1300897-21
LS-D5B	10/21/2013	10:20	2-4	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.7	31.2	25-Oct-13	1300897-21
LS-D5C	10/21/2013	10:20	4-6	Composite	Nitrate/Nitrite Nitrogen	<0.04	mg/kg dry	EPA 353.2	5	0.04	1.3	28-Oct-13	1300897-22
LS-D5C	10/21/2013	10:20	4-6	Composite	Percent Solids	78.7		SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-22
LS-D5C	10/21/2013	10:20	4-6	Composite	Phosphorus (Total)	374.1	mg/kg dry	EPA 6010B	45.81	1	5.8	24-Oct-13	1300897-22
LS-D5C	10/21/2013	10:20	4-6	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.7	31.8	25-Oct-13	1300897-22
LS-D6A	10/21/2013	9:30	0-2	Composite	Nitrate/Nitrite Nitrogen	1.5	mg/kg dry	EPA 353.2	5	0.04	1.1	28-Oct-13	1300897-23
LS-D6A	10/21/2013	9:30	0-2	Composite	Percent Solids	91.05	,	SM 2540 G	1	0.01	0.01		1300897-23
LS-D6A	10/21/2013	9:30	0-2	Composite	Phosphorus (Total)	481.4	mg/kg dry	EPA 6010B	50.28	0.9	5.5	24-Oct-13	1300897-23

Station	Date	Time	Depth	SampleSource	Analyte	Result	Units	Method	DF	MDL	MRL	AnalysisDate	LabNumber
LS-D6A	10/21/2013	9:30	0-2	Composite	Total Kjeldahl Nitrogen	563	mg/kg dry	PAI-DK 01	5	1.5	27.5	25-Oct-13	1300897-23
LS-D6B	10/21/2013	9:30	2-4	Composite	Nitrate/Nitrite Nitrogen	1.4	mg/kg dry	EPA 353.2	5	0.04	1.3	28-Oct-13	1300897-24
LS-D6B	10/21/2013	9:30	2-4	Composite	Percent Solids	79.44	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-24
LS-D6B	10/21/2013	9:30	2-4	Composite	Phosphorus (Total)	409.4	mg/kg dry	EPA 6010B	51.65	1.1	6.5	24-Oct-13	1300897-24
LS-D6B	10/21/2013	9:30	2-4	Composite	Total Kjeldahl Nitrogen	290	mg/kg dry	PAI-DK 01	5	1.7	31.5	25-Oct-13	1300897-24
LS-D6C	10/21/2013	9:30	4-6	Composite	Nitrate/Nitrite Nitrogen	< 0.05	mg/kg dry	EPA 353.2	5	0.05	1.4	28-Oct-13	1300897-25
LS-D6C	10/21/2013	9:30	4-6	Composite	Percent Solids	72.7	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-25
LS-D6C	10/21/2013	9:30	4-6	Composite	Phosphorus (Total)		mg/kg dry	EPA 6010B	49.29	1.2	6.8	24-Oct-13	1300897-25
LS-D6C	10/21/2013	9:30	4-6	Composite	Total Kjeldahl Nitrogen	769	mg/kg dry	PAI-DK 01	5	1.9	34.4	25-Oct-13	1300897-25
LS-D6D	10/21/2013	9:30	6-8	Composite	Nitrate/Nitrite Nitrogen	<0.05	mg/kg dry	EPA 353.2	5	0.05	1.4	28-Oct-13	1300897-26
LS-D6D	10/21/2013	9:30	6-8	Composite	Percent Solids	72.54		SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-26
LS-D6D	10/21/2013	9:30	6-8	Composite	Phosphorus (Total)	583.7	mg/kg dry	EPA 6010B	51.12	1.2	7	24-Oct-13	1300897-26
LS-D6D	10/21/2013	9:30	6-8	Composite	Total Kjeldahl Nitrogen	652	mg/kg dry	PAI-DK 01	5	1.9	34.5	25-Oct-13	1300897-26
LS-D6E	10/21/2013	9:30	8-10	Composite	Nitrate/Nitrite Nitrogen	<0.05	mg/kg dry	EPA 353.2	5	0.05	1.3	28-Oct-13	1300897-27
LS-D6E	10/21/2013	9:30	8-10	Composite	Percent Solids	76.55	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-27
LS-D6E	10/21/2013	9:30	8-10	Composite	Phosphorus (Total)	515.9	mg/kg dry	EPA 6010B	51.41	1.1	6.7	24-Oct-13	1300897-27
LS-D6E	10/21/2013	9:30	8-10	Composite	Total Kjeldahl Nitrogen	387	mg/kg dry	PAI-DK 01	5	1.8	32.7	25-Oct-13	1300897-27
LS-D7A	10/16/2013	15:00	0-2	Composite	Nitrate/Nitrite Nitrogen	< 0.04	mg/kg dry	EPA 353.2	5	0.04	1.2	28-Oct-13	1300897-28
LS-D7A	10/16/2013	15:00	0-2	Composite	Percent Solids	86.09	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-28
LS-D7A	10/16/2013	15:00	0-2	Composite	Phosphorus (Total)	460.7	mg/kg dry	EPA 6010B	50.15	1	5.8	24-Oct-13	1300897-28
LS-D7A	10/16/2013	15:00	0-2	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.6	29		1300897-28
LS-D7B	10/16/2013	15:00	2-4	Composite	Nitrate/Nitrite Nitrogen	< 0.04	mg/kg dry	EPA 353.2	5	0.04	1.1	28-Oct-13	1300897-29
LS-D7B	10/16/2013	15:00	2-4	Composite	Percent Solids	95.11	%	SM 2540 G	1	0.01	0.01		1300897-29
LS-D7B	10/16/2013	15:00	2-4	Composite	Phosphorus (Total)	351.4	mg/kg dry	EPA 6010B	50.25	0.9	5.3	24-Oct-13	1300897-29
LS-D7B	10/16/2013	15:00	2-4	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.4	26.3		1300897-29
LS-D7C	10/16/2013	15:00	4-6	Composite	Nitrate/Nitrite Nitrogen	<0.04	mg/kg dry	EPA 353.2	5	0.04	1	28-Oct-13	1300897-30
LS-D7C	10/16/2013	15:00	4-6	Composite	Percent Solids	96.33		SM 2540 G	1	0.01	0.01		1300897-30
LS-D7C	10/16/2013	15:00	4-6	Composite	Phosphorus (Total)		mg/kg dry	EPA 6010B	48.43	0.9	5	24-Oct-13	1300897-30
LS-D7C	10/16/2013	15:00	4-6	Composite	Total Kjeldahl Nitrogen			PAI-DK 01	5	1.4	26		1300897-30
LS-D7D	10/16/2013	15:00	6-8	Composite	Nitrate/Nitrite Nitrogen	< 0.04	mg/kg dry	EPA 353.2	5	0.04	1.1	28-Oct-13	1300897-31
LS-D7D	10/16/2013	15:00	6-8	Composite	Percent Solids	88.56		SM 2540 G	1	0.01	0.01		1300897-31
LS-D7D	10/16/2013	15:00	6-8	Composite	Phosphorus (Total)	271.2	mg/kg dry	EPA 6010B	46.13	0.9	5.2	24-Oct-13	1300897-31
LS-D7D	10/16/2013	15:00	6-8	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.5	28.2	25-Oct-13	1300897-31
LS-D7E	10/16/2013	15:00	8-10		Nitrate/Nitrite Nitrogen	<0.04	mg/kg dry	EPA 353.2	5	0.04	1.3	28-Oct-13	1300897-32
LS-D7E	10/16/2013	15:00	8-10	Composite	Percent Solids	79.98		SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-32
LS-D7E	10/16/2013	15:00	8-10	Composite	Phosphorus (Total)	331.7	mg/kg dry	EPA 6010B	49.29	1	6.2		1300897-32
LS-D7E	10/16/2013	15:00	8-10	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.7	31.3	25-Oct-13	1300897-32
LS-D8A	10/16/2013	13:00	0-2	Composite	Nitrate/Nitrite Nitrogen		mg/kg dry	EPA 353.2	5		1.2		1300897-33
LS-D8A	10/16/2013	13:00	0-2	Composite	Percent Solids	85.19	0 0	SM 2540 G	1	0.01	0.01		1300897-33
LS-D8A	10/16/2013	13:00	0-2	Composite	Phosphorus (Total)		mg/kg dry	EPA 6010B	47.53	0.9	5.6		1300897-33
LS-D8A	10/16/2013	13:00	0-2	Composite	Total Kjeldahl Nitrogen		mg/kg dry	PAI-DK 01	5	1.6	29.3		1300897-33
LS-D8B	10/16/2013	13:00	2-4	Composite	Nitrate/Nitrite Nitrogen		mg/kg dry	EPA 353.2	5	0.04	1.2		1300897-34
LS-D8B	10/16/2013	13:00	2-4	Composite	Percent Solids	82.82		SM 2540 G	1	0.01	0.01		1300897-34
LS-D8B	10/16/2013	13:00	2-4	Composite	Phosphorus (Total)	575.1	mg/kg dry	EPA 6010B	48.92	1	5.9		1300897-34
LS-D8B	10/16/2013	13:00	2-4	Composite	Total Kjeldahl Nitrogen	_	mg/kg dry	PAI-DK 01	5	1.6	30.2		1300897-34
LS-D8C	10/16/2013	13:00	4-6	Composite	Nitrate/Nitrite Nitrogen	<0.04		EPA 353.2	5		1.1		1300897-35
F2-D8C	10/16/2013	13:00	4-0	Composite	initiate/inititle initiogen	<0.04	mg/kg ary	EPA 333.2	5	0.04	1.1	20-001-13	1300097-35

Station	Date	Time	Depth	SampleSource	Analyte	Result	Units	Method	DF	MDL	MRL	AnalysisDate	LabNumber
LS-D8C	10/16/2013	13:00	4-6	Composite	Percent Solids	89.18	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-35
LS-D8C	10/16/2013	13:00	4-6	Composite	Phosphorus (Total)	502.9	mg/kg dry	EPA 6010B	48.8	0.9	5.5	24-Oct-13	1300897-35
LS-D8C	10/16/2013	13:00	4-6	Composite	Total Kjeldahl Nitrogen	261	mg/kg dry	PAI-DK 01	5	1.5	28	25-Oct-13	1300897-35
LS-D8D	10/16/2013	13:00	6-8	Composite	Nitrate/Nitrite Nitrogen	< 0.05	mg/kg dry	EPA 353.2	5	0.05	1.3	28-Oct-13	1300897-36
LS-D8D	10/16/2013	13:00	6-8	Composite	Percent Solids	77.76	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-36
LS-D8D	10/16/2013	13:00	6-8	Composite	Phosphorus (Total)	574.6	mg/kg dry	EPA 6010B	46.02	1	5.9	24-Oct-13	1300897-36
LS-D8D	10/16/2013	13:00	6-8	Composite	Total Kjeldahl Nitrogen	440	mg/kg dry	PAI-DK 01	5	1.8	32.2	25-Oct-13	1300897-36
LS-D8E	10/16/2013	13:00	8-10	Composite	Nitrate/Nitrite Nitrogen	< 0.05	mg/kg dry	EPA 353.2	5	0.05	1.3	28-Oct-13	1300897-37
LS-D8E	10/16/2013	13:00	8-10	Composite	Percent Solids	76.27	%	SM 2540 G	1	0.01	0.01	25-Oct-13	1300897-37
LS-D8E	10/16/2013	13:00	8-10	Composite	Phosphorus (Total)	501.1	mg/kg dry	EPA 6010B	47.82	1.1	6.3	24-Oct-13	1300897-37
LS-D8E	10/16/2013	13:00	8-10	Composite	Total Kjeldahl Nitrogen	288	mg/kg dry	PAI-DK 01	5	1.8	32.8	25-Oct-13	1300897-37

Attachment 4

Phosphorus in Iowa Soils

PHOSPHORUS IN IOWA SOILS

T. E. Fenton Agronomy Department Iowa State University December 3, 1999 tefenton@iastate.edu

Introduction

Phosphorus is a key element in all living things. It is also a major fertilizer element and a major component of manure. Excess phosphorus in bodies of water causes growth of algae and other aquatic plants and thus is of environmental concern. Phosphorus is also a dynamic element in soil genesis. The amount, distribution, and chemical composition of phosphorus in soils are closely related to the classic factors of soil formation-climate, organisms, parent material, topography, and time. Also, in the past 150 years in Iowa, human influence on soils and landscapes is an additional variable that contributes to changes in soil profile characteristics and properties. These changes include but are not limited to the properties associated with accelerated erosion and related deposition, fertilization, cultivation and resulting decrease in organic matter, and changes in the water regimes of the whole soil due to artificial drainage.

In 1940, Pearson, Spry, and Pierre published a paper entitled "The Vertical Distribution of Total and Dilute Acid-soluble Phosphorus in Twelve Iowa Soil Profiles". Since that time there has been an interest in understanding and predicting the phosphorus regimes of Iowa soils. The paper cited and other subsequent research formed the basis for the refinement of soil test recommendations that recognize low and high subsoil P categories. This distinction results in the range of soil test categories being modified to acknowledge the difference in available subsoil P. For example, the very low soil test category for P for corn production is 0-8 ppm for soils with low subsoil P but 0-5 for soils with high subsoil P. The differences in subsoil P are directly related to the composition of the P compounds in soils which in turn is related to the factors of soil formation. Therefore, it is important to understand the transformations and dynamics of P that occur in soil ecosystems.

Phosphorus Forms in Soil

Terminology used to describe various forms of P in the soil is diverse but most researchers use terminology related to the extractant used. Smeck (1985) used the terms soluble, labile, primary minerals, secondary minerals, organic and occluded to describe P forms. Soluble P is extractable with water or a dilute salt. Labile P is isotopically exchangeable or anion resin extractable phosphorus which is in equilibrium with P in the soil solution. Primary minerals are apatites which are acid-extractable. Secondary P minerals include minerals with P chemisorbed to their surfaces (commonly Fe and Al oxides and carbonates) as well as minerals formed by low temperature crystallation which contain P as a structural component. Secondary P minerals can be viewed as dictating long-term sluggish movement toward equilibria. Organic P is that P associated with organic matter. Occluded P is used to describe P that is physically encapsulated by minerals which have no P in their structure.

Transformations

A version of the P cycle is shown in Figure 1. The initial source of all P in soils is the primary minerals present in the parent material. Apatite is the most common primary mineral to serve as a source for P. Its solubility is increased under acid conditions and soluble P is released. The soluble P may be leached, taken up by plants or microorganisms, enter the labile pool, or be transformed into secondary minerals. Soil properties which determine the anion exchange capacity control the size of the potential labile P pool. However, the actual quantity of the labile P is related to the solubility product and dissolution of kinetics of secondary P minerals. Some secondary P forms (dicalcium phosphate dihydrate or octocalcium phosphate rapidly equilibrate with labile and soluble P but other such as hydroxyapatite equilibrate so slowly that equilibrium is seldom attained (Murrman and Peech, 1969). While it is generally thought that P is relatively immobile in soils, this is not true over the longer term. Phosphorus profiles are interpreted in term of eluvial and illuvial horizons (Runge and Riecken, 1966; Fenton et al., 1967)

Soil Test Phosphorus (STP)

Soil test data reported in this paper unless otherwise specified were determined by the Bray 1 method. This method uses a weakly acid extractant and solubilized P in two ways: 1) the acid extractant (pH 3) solubilizes mostly acid-soluble Caphosphates and some Al- and Fe-phosphates that become soluble at low pH values and 2) the addition of NH_4F ions complexes the Fe and Al in the soil solution. Other methods will solubilize different amounts of P. However, the importance of any method is the ability to extract a representative portion of the P available to the plant that in turn can be used to predict the availability of soil P to the plant under a variety of conditions. Figure 2 shows the relationship between pH and phosphorus solubility in the soil. The dashed line shows the upper limit of available P in solution and illustrates the reason that for soils with 2:1 type clay minerals the optimum pH for P availability is in the pH range of 6.5 to 7.0. The dominant P form at this pH is $H_2PO_4^-$ and HPO_4^- .

Birchett (1974) studied the relationship of the Bray, Olsen, and Resin extractable P for soils of southwest Iowa. Data for three southwestern Iowa soils and a comparison with a Tama soil from eastern Iowa are shown in Figure 3. In all the soils studied, less P was extracted by the Olsen extractant than by the Bray or Resin extractant. However, the slopes of the STP depth-distribution curves are similar. Two major exceptions were the Rathbun and Weller profiles in which certain horizons had greater amounts of extractable P by the Resin method than by the Bray. Similar but smaller differences were reported for the Kniffin profile. These difference were attributed to the possibility that the Resin method prevented the readsorption of dissolved P by the clay surfaces. The ratio of the amount of STP extracted varied with horizon. The Olsen method extracted relatively more P with increasing depth in the profiles suggesting that this method extracts a larger portion of the Ca-P. The Olsen method had a higher correlation with plant-available P in the C horizon than the Bray method. For the subsoils, the simple correlations between Bray P and Olson P decreased with horizon depth and was associated with the decreasing correlations with depth with slight increases in average soil pH.

As the soil depth and soil pH increased, the ratio of Ca-phosphates to the Fe-and Al-phosphates increased, the relative effectiveness of the Bray to the Olsen method decreased. Addition of the soil pH variable increased the correlation between the two but horizon depth was not included in the regression and may also have been a factor. Miller (1974) studied Tama profiles in eastern Iowa on different landscape positions. He compared the Bray 1 and Bray 2 extraction methods. The Bray 2 method uses 1N HCL as compared to .025 N HCL for the Bray 1. He reported that the Bray 2 method extracted 1.4 to 1.7 times more STP than the Bray 1 method in the sola of the well and somewhat poorly soils studied. Below forty inches, the Bray 2 method extracted 2.4 to 2.7 times more STP than Bray 1. When pH values increased to near neutral the Bray 1 decreased by 50% and the Bray 2 STP increased by several hundred percent. Athe increase in Ca-P with depth is severall times greater in the near neutral range than in acidic soil environments.

Effect of Profile differentiation on STP

The soil forming factors important in profile differentiation are climate and time. Climatic factors of temperature and precipitation are especially important in chemical reactions in the soil. Precipitation provides the soil water necessary for chemical reactions and leaching. Temperature is an important factor in the speed of reactions. Time is an important factor in the stage of weathering, usually described in terms of youth, maturity and old age. Birchett described the depth-distribution of STP for soils formed in loess parent material under prairie vegetation. Three zones, designated as zones 1, 2, and 3 are shown in Figure 4 for a Marshall soil with STP values determined by the Bray 1 method. He also studied transition and forested soils from southern Iowa. Soils formed under forest vegetation have the same general depth curve for STP but have greater amounts of STP. Zone 1 was described as the surface or A1 horizon for virgin soils or the Ap horizon for cultivated soils. It is the part of the soil where cropping, return of plant residues, and the additional of fertilizers and manure can cause large variation in STP. However, there are also other factors that affect P availability to plants. Availability is a function not only of the amount in solution but also the amount of water present in the soil and the distance the P must move to reach the root.

Zone 2 is the part of the STP depth curve with the lowest amount of P. It is generally in those horizons immediately beneath the Ap or A1 horizons and includes either parts or all of the E, A2.., and upper part of the B horizon. This depth is often between 6 and 24 inches for most of the profiles studied by Birchett.

Below the minimum STP levels, the amount of STP increases to a zone of maximum solubility that is usually in the lower B horizon or the upper B horizon. In many of the profiles studied, this zone was at a depth of 36 to 48 inches. If free

carbonates were encountered, above this depth very low levels of STP were present. In these cases, the maximum solubility occurred in less alkaline or more acid horizons closer to the soil surface.

Ida, Monona, Marshall, and Sharpsburg comprise a developmental sequence of loess-derived soils formed under prairie vegetation. Ida soils have free carbonates throughout their profile. Ida soils are low in available P. Birchett reported that for the Monona soils studied there was a wide range of Bray-extractable P that were apparently related to the degree of weathering. The Monona profiles with high pH and shallower depth to carbonates had low amounts of extractable P and were close to the Ida soils in their characteristics. As the soil properties of Monona came closer to Marshall soils, extractable P increased. These relationships result in range of extractable P in Monona soils. The same trends were reported for Marshall soils (Figure 5A). Those profiles sampled in the Monona-Marshall transitional area had P distributions similar to the Monona profiles while those in the Marshall-Sharpsburg transition area had P distributions similar to those in the modal Sharpsburg area. The differences in amounts of extractable P were apparently related to soil pH. Those profiles with high amounts of extractable P had pH values ranging from 5.67-6.06 in the 24 to 48 inch horizons while those profiles with lower amounts of extractable P had pH values ranging from 6.31 to 6.87. It appeared that the lower pH values increased the solubility of Ca-phosphates in these soils. The largest amount of extractable P was in the C1 horizon, at the base of the solum, where weathering had removed the free carbonates and the pH was slightly below neutrality.

Soil Test P and Vegetation

The early work of Pearson et al., 1940 demonstrated the effect of different native vegetation on the STP content of soils. However, while native vegetation may be the most obvious variable present, soil genesis theory uses the term organisms which is a more holistic approach and sets soil as a part of the ecosystem. STP is responsive to the total ecosystem and it is difficult to separate the variables but the soil, as influenced by the dominant vegetative type and associated environment, is the component tied most closely to the STP. Within a biosequence (a sequence of soil alike in all soil forming factors except vegetation) the forested member has the highest content of STP, the transitional member (both grass and forest) is intermediate and the prairie soil has the least. This comparison is true in relative amounts as shown in Figure 5B. However, note that the STP content of Tama, a loess-derived prairie soil, is higher than that of Kniffin, a loess-derived forested soil. However, the Kniffin soils are more highly weathered than the Tama soils.

Kazemi (1983) summarized soil test data from 251 profiles located in the eastern part of Iowa. Counties included were Bremer, Howard Fayette, Linn, Muscatine, and Keokuk. The major objective of this study was to study the effect of soil property differences, including native vegetation, on the amount and depth-distribution of STP. Multiple regression techniques were used to develop prediction equations for STP. The native vegetation had a dominant effect on STP and decreased from forest to prairie (Figure 6 & 7). Eroded soils had lower subsoil STP levels than uneroded soils. The STP decreased from well to poorly drained soils(Figure 8). Runge and Riecken (1966) also reported higher amounts of available P in somewhat poor and moderately well drained soils as compared to poorly drained soils. This trend was related to higher pH values in the poorly drained soils in both studies. Kazemi also found that loess parent material had higher subsoil STP than any other group of parent materials, till parent material had the lowest STP and STP values decreased linearly from convex to concave slopes.

Soil Test P and Parent Material

In general, soil formed in loess have higher contents of STP when all other soil forming factors are constant. The differences between Tama (loess-derived), Kenyon (till-derived) and Clarion (till-derived) are shown in Figure 9. Figure 10 presents a summary of the analyses by Kazemi (1983) relating STP depth distribution to major parent materials in Iowa. Eolian deposits (excluding loess) were lowest in STP. Loess was highest. Alluvium, till, and loess over till were intermediate in STP content.

Total Phosphorus

Major environmental concern for soil phosphorus involve phosphorus leaving a soil surface in the form of dissolved P in

runoff or with the soil particle in erosional processes. Therefore, a knowledge of the total phosphorus content of soils and the depth distribution of total phosphorus in different soils are important parameters to understand. While it is generally thought that P is relatively immobile in soils, this is not true over the longer term. Total phosphorus profiles, such as the ones shown in Figure 11, are interpreted in term of eluvial and illuvial horizons. Two deep profiles, one beneath Marshall and the other beneath Tama show the depth trends expected in well drained soils formed in thick loess, one in western Iowa (Potawattamie County) and the other in eastern Iowa (Tama County).

Vegetation (Biotic Factor)

Biosequence effects on the genesis and resulting differences in soil phosphorus have long been recognized (Pearson et al., 1940; Fenton et al., 1967; Mausbach, 1969; Tembhare, 1973; Collins, 1977; Miller, 1974. Fenton et al., 1967 arrayed soil profile data by biosequences to test the effect of native vegetation on the phosphorus characteristics of soils. Total phosphorus was high in the surface horizon, decreases to a minimum and then increased with depth within all members of the biosequences. The general trend of the distribution is similar whether the parent material is loess or glacial till. The depth distributions of the well and moderately drained loess-derived soils are shown in Figure 12 and the well drained till-derived soils are shown in Figure 13. Depth to the TP minimum is most shallow in the forested member of the biosequence (Table 1). The TP minimum within a biosequence is always less in the transitional or forested member as compared to the prairie member.

Within a biosequence the forested soil also has the lowest content of less than 2 micron clay in the minimum TP horizon. The TP minima in the prairie soil profiles are more closely associated with the maximum clay content within the profile. This trend is illustrated by the data in Table 2. The average clay content in the horizon of minimum TP decreases from 37.2% for the prairie soils to 20.1% for the forest soils. The range in the mean maximum clay within the profiles varies within a narrow range of 38 to 40.6%. The trend is shown in Table 2. In the forested soils and the transitional Grundy soils the TP minima coincides with the part of the zone described as the E horizon. In all other soils, except for the transitional Grundy soil, the TP minimum is in the B horizon and it is most closely associated with the zone of maximum clay in the prairie soils (Table 2). The data relating minimum TP values to layer of maximum clay content in prairie soils is in agreement with the observations of Runge and Riecken (1966). In the transition and forested members the minimum TP value are more closely associated with the upper B or E horizon and not the zone of maximum clay.

Figure 12 shows the depth distribution of total P for a number of well to moderately well drained loess-derived biosequence. There are differences in the depth distributions related to the native vegetation. Forested soils have the greatest amount of total P to a depth of 40 inches as shown in Table 1. In general, for well drained soils, where we expect the net vector of water movement to be downward, the P distributions are more predictable. Figure 14 shows the loess-derived somewhat poorly drained Muscatine and Mahaske biosequences and Figure 15 shows the poorly drained landscape associates of these soils. Figure 13 shows the total P distribution in two till-derived biosequences. The Clarion and Kenyon biosequence members are well-drained and have similar depth distributions of total P as the well-drained loess-derived soils but lower amounts. The till-derived somewhat poorly drained Nicollet and the poorly drained Webster biosequence are also shown in Figure 13. These soils have higher fluctuating water tables and thus the depth distribution of total P in these soils is less predicable that for the better drained soils.

As soil horizon differentiation increases, the P minerals change in form and distribution. With respect to phosphorus, native vegetation differences are related to forms of phosphorus. Mausbach (1969) reported that the levels of Caphosphates decreased and the Fe and Al-phosphates increased progressively from the prairie soils to the transitions and to the forested soils (Figure 16). This increase in Fe and Al phosphates was associated with decreasing pH from the prairie to the forest soils. This relationship is illustrated in Figure 17 which shows the relationship between pH and the ratio of Fe-P + Al-P divided by Ca-P for a number of Iowa soils. Hsu and Jackson (1960) found that Fe and Al-phosphates are stable at pH values lower than the pH values at which Ca-phosphates are stable. The lower pH under forest vegetation contributes to increased weathering rates. Smeck and Runge (1971) showed increasing aluminum, iron and reductant soluble P and decreasing calcium P along a traverse from a Haplaquoll to an Albaqualf at the end of the transect. They also found a progressive increase in STP along the same traverse. P availability increased as horizon differentiation increased.

Westin and Buntley (1966a, 1967) reported that the cooler drier Borolls had less Fe-P and reductant P and more Ca-P than the Ustolls in South Dakota.

Parent Material

Loess generally has higher contents of TP than till (see Figures 12 & 13). Pearson et al. 1940, reported that the glacial till they studied contained about 300 ppm of TP while the loess averaged about 700 ppm. These difference related to parent material have also been reported in subsequent research in Iowa. However, the actual difference in the amount of total of phosphorus present is less if bulk density is considered. An acre foot of till (assuming a bulk density of 1.5) and using the 300 ppm content has 122,316 pounds of P while an acre foot of loess has 247,350 pounds. Corrected on this basis the loess has approximately twice as much TP rather than 2.3 when expressed in ppm. However, the TP content of the loess ranges from the value cited above to lower values where the loess sections have been weathered. For example, Seymour soils in southeastern Iowa formed in loess but the TP content of the least altered loess is 540 ppm while in western Iowa beneath the Marshall soil TP contents of 850 ppm are present. TP content of alluvium has a wide range. TP contents are low in more weathered alluvium and highest in calcareous alluvium.

Time and Topography

The plot shown in Figure 18 shows the effect of time and topography on TP. Clarinda is a paleosol derived from pre-Illinoian till. Note the low content of TP in this soil. The low TP content is attributed to the advanced stage of weathering of this soil. The Sperry soil is a loess-derived very poorly drained soil in eastern Iowa. It occurs in closed depressions and has the highest TP contents that I found in the Iowa data. Smeck, 1973; Walker and Syers, 1976; Smeck and Runge, 1971 showed that phosphorus is translocated within the soil profile and landscape within a pedologic time-frame. Smeck (1985) reported that of the soils studied in Illinois, in each toposequence the TP content was highest in soils on the low end of the hydrologic gradient. The content of TP in Sperry supports that interpretation. Theoretical changes in P over time are shown in Figure 19. Note that eventually all the primary P minerals will weather. Walker and Syers (1976) suggested that for the soil conditions they studied, this process would take about 22,000 years. Occluded P continues to increase at the expense of secondary P until eventually only occluded P and organic P remain.

Organic P

Kosse (1966) studied organic carbon/organic phosphorus ratios in selected Iowa soils. Values for surface horizons of the poorly drained soils studied ranged from 90 to 152 and were markedly higher than for the somewhat poorly, moderately well and well drained soils. It has been well established that the driving force for conversion of primary to secondary and occluded forms is decreasing pH due to weathering and leaching of the soil. However, the driving force for organic P has not been as well documented. Early work suggested a direct relationship between organic matter and organic P content of a soil. However, Smeck and Runge (1972) determined that organic matter production may be limited by factors other than P availability. Low levels of organic matter content occur in some soils with high levels of available P. Organic P is more stable at low pH rather than high pH. Liming tends to allow breakdown and mineralization of org P. Both N and org P decline with cultivation. Organic P is held by covalent bonds and does not ionize. Decomposition breaks down O2 bonds and the P can mineralize. The adsorption of P is stronger than that for cations. Figure 19 shows an idealized diagram of soil development related to organic P and organic C.

Summary-Soil Test Phosphorus and Total Phosphorus

Figure 20 shows a plot of TP and STP for a Tama soil in Iowa. As might be expected, there is no direct relationship between TP and STP. However, TP is a key element in soil genesis. As soils develop, the TP undergoes changes that are related to the weathering environment. We expect the amount and forms of TP to change with soil-forming processes. It was demonstrated that the driving force for conversion of primary to secondary and occluded forms is decreasing pH due to weathering and leaching of the soil. STP was shown to be highest in soils formed under forest vegetation and this in large part is due to the forms of phosphorus which in turn is related to pH and the weathering process. Forest soils are more acid and the weathering of clay minerals release Fe and Al which in turn react with the phosphorus. The amount of STP extracted for a given soil is related to the combination of P forms and pH (Figure 2).

As discussed by Voss and Griffith, agriculture has been designated as the primary source of phosphorus entering inland streams, lakes, and water impoundments. Phosphorus leaves agricultural fields as dissolved phosphorus and particulate phosphorus attached to soil sediment. Crop production cultural practices were cited as major factors in the concentration and amount of P in the runoff. Thus far, I have used primarily soil series names in this paper. However, on a landscape basis, the soil unit that provides the most information is the soil map unit, a combination of the soil series and phases including surface texture, erosion phase and slope class. It is at this level that nutrient management plans should be based. Soil map units within one soil series exhibit wide ranges in organic matter content, clay content, slope gradient, length, and configuration all of which are factors that contribute to the amount of dissolved and particulate phosphorus moved in runoff. For example most of the well and moderately well drained soil series have several slope and erosion phases. The differences described in the soil series description state the following: "The thickness of the A horizon, depth to subhorizon highest in clay, maximum percent clay, thickness of B horizon, depth to carbonates, depth to mottling and solum thickness usually decrease as gradient increases on convex slopes". These factors indicate that each soil map unit has a distinct set of characteristics that will interact with the type of cultural practices used for any field. These are all important properties that should be a part of any soil management decision-making process.

Soil Survey

Soil survey involves the mapping, classification, correlation, and interpretation of soils. The first soil survey in Iowa was in the Dubuque County area but did not include the entire county. The field work was done in 1902 and the report was published in 1903. Since that time, most Iowa counties have had at least two soil surveys completed and some have had three. The basic factors of soil formation have not changed but the use of the soils for intensive agriculture has resulted in changes in some soil properties, especially of the surface horizons. However, generally factors other than soil differences have been responsible for multiple soil surveys over one area. Over time, our concept of soil has changed. Early soil scientists with a background in geology considered the soil to be primarily that part of the earth's surface that had been darkened by the addition of organic matter., Our concept of soil has evolved so that soil now is considered a natural body made up of several horizons or layers that are genetically related to the soil forming factors under which the soil has developed. Total analyses of soils for phosphorus and potassium was a common practice during the early 1900's. Later, it was learned that it was not the total amount of a nutrient that was important for plant growth but the amount that was available to the plant. Other major factors in resurveys were the scale and the base map used.

The early soil maps were generally made at a scale of 1 inch per mile on a plane-table base map. In the late 1930's the use of aerial photographs as base maps for soil survey was implemented. Most of the surveys were made at a scale of 4 inches per mile and most of the modern surveys we have in Iowa were made at that scale. Beginning in the 1990's, orthophotographs were used as base maps and the field mapping is presently being done at a scale of 1:12,000 or 5.28 inches per mile.

Availability of Soil Information

Soil surveys are available for all Iowa counties in published reports and presently 95 of the 99 counties also have the same information available in digital format. Many digital soil maps of Iowa are available on the internet at http://www.ia.nrcs.usda.gov/

To access the soil information select-Soils, Soils Information, and Digital Soil Survey Data From Iowa Cooperative Soil Survey on successive screens. Data bases giving soil properties and interpretations are available at the same site. The Iowa State University Extension home page also contains soil information as well as a link to the digital soil maps and databases. The home page address is:

http://extension.agron.iastate.edu/soils/soilsurv.html

Descriptions for all soil series in the U.S. are located at: http://www.statlab.iastate.edu/cgi-bin/osd/osdname.cgi
For those who do not have access to the internet, the digital soil information and associated data bases are available on
CD-ROM or diskettes. The digital soil information is available in several different formats and is suitable for use in most
Geographic Information Systems (GIS). For those users not interested in using a GIS the digital information may be used
with the ISOIL program which is our software package for handling soil maps and data. Contact me at the above address if
you have questions on the availability of soil information in Iowa.




Figure 1. Phosphorus transformations in natural soil ecosystems. From Smeck (1985)




Figure 2. Relative proportion of phosphate ions in solution at different pH levels in a Ca-H₃PO₂ system. From Troosh, 1993.




Figure 3. Comparison of three phosphorus extraction methods. From Birchett, 1974.




Figure 4. Zones in STP depth-distribution for deep locss. From Birchett, 1974.




Figure 5. STP depth distribution for selected losss-derived soils. From Birchett, 1974.




Figure 6. Predicted STP depth distribution for locss-derived biosequences. From Kazemi, 1983.




Figure 7. STP depth distribution for Tama and Otley biosequences.





Figure 8. Predicted STP depth distribution for well drained (30) and poorly (70) drained losss and till-derived soils. From Kazemi, 1983.







Figure 10. Predicted STP depth distribution for Iowa soil parent materials. From Kazemi, 1983.






Figure 12. Depth distribution of TP for losss-derived moderately well and well drained soils.




Figure 13. Depth distribution of TP for till-derived moderately well, well desired stills, somewhat poorly and poorly desired stills.




Figure 14. Depth distribution of TP for losss-derived somewhat poorly drained soils.




Figure 15. Depth distribution of TP for losss-derived poorly drained soils.






Figure 16. Phosphorus fractions in the Tama and Garwin biosequences. From Maushach, 1969.








Figure 19. Changes in forms and amount of phosphorus with time. From Walker and Syers, 1976.




Table 1. Average total P per 2.54 cm, total P minimum, and depth to total P minimum

BIOSEQUENCE	X TOTAL P (TO 129.54 CM)*			TOTAL P MIN. (PPK)			DEPTH TO TOTAL P MIN.		
W TO MW DRAINED	P	T	F	þ	T	F	P	T	r
TAMA	525	508	587	420	348	396	53.3	41.9	29.2
OTLEY	517	510	571	384	372	404	73.7	47.0	26.7
GRUNDY	543	<u>524</u>	587	345	320	258	44.3	26.7	17.8
SP DRAINED									
MUSCATINE	586	588	<u>517</u>	362	424	344	77.5	54.6	22.9
Mahaska	536	464	501	399	285	299	53.3	35.6	33.0
PDRAINED									
Garu in	640	488	508	513	260	310	57.2	27.9	25.4
TAINTOR	522	473	475	322	276	190	49.5	29.2	31.8
HAIG	<u>488</u>	492	518	300	276	220	40.6	33.0	29.Z
W DRAINED									
Kenyon	474	-	525	384	44	366	39.4	**·	16.5
CLARION	412*	302	431	320	200	260	45.7	41.9	22.9
F DRAINED									
NICOLLET	486	352	294	320	320	220	74.9	29.2	39.4
DRAINED"									
Webster	<u> 375</u>	504	388	260	420	200	48.3	53.3	44.5

^{*}CLARION, NICOLLET, AND WEBSTER BIGSEQUENCE DATA BASED ON A TOTAL DEPTE OF 101.6 CM.

Table 2. DEPTH TO (TP) MIN. AND CLAY CONTENT AT THAT DEPTH

MOTERATORY AND SHALL HAVE AND		EPTH T TP) MI	_	······································	. 5.	***************************************	
BIOSEQUENCE	<u> </u>	(CM)		< 2μ (7.)			
M TO MW							
<u>DRAINED</u>	P	T	F	P	I	F	
LOESS							
TAMA	53.3	41.9	29.2	31.0	31.1	20.5	
OTLEY	73.7	47.0	26.7	36.2	32.8	22,1	
GRUNDY	44.5	26.7	17.8	44.5	27.0	17.6	
TILL							
KENYON	39.4	aimi	16.5	24.5	**	11.1	
CLARION	45.7	41.9	22.9	25.8	27.5	24.2	

	DI	PTH :	ro				
	(1	(P) M	IN.	< 2µ			
BIOSEQUENCE	<u> </u>	(CM)	·				
SP DRAINED	P	eq.	F	p	T	F	
LOESS							
MUSCATINE	77.5	54.6	22.9	32.0	32.1	21.0	
Hahaska	53.3	35.6	33.0	39.6	28.2	28.3	
TILL							
nicollet	74.9	<u> 29.2</u>	39.4	33.1	27.1	20.0	
P DRAINED							
LOESS							
GARWIN	57.2	27.9	25.4	35.2	24.8	28.3	
TAINTOR			31.8				
HAIG			29.2				
TILL							
WEBSTER	48.3	53,3	44.5	34.0	34.0	35.4	

SELECTED BIBLIOGRAPHY ON SOIL PHOSPHORUS

Adams, J. A., and T. W. Walker. 1975. Some properties of a chronotoposequence of soils from granite in New Zealand - 2. Forms and amounts of phosphorus. Geoderma 13:41-51.

Altschuler, Z. S. 1973. Weathering of phosphate deposits—geochemical and environmental aspects. In E. J. Griffith, A. Beeton, J. M. Spencer, and D. T. Mitchell (eds.) Environmental phosphorus handbook. John Wiley and Sons, New York.

A l-Abbas, A. H. and S. A. Barber. 1964. A soil test for phosphorus based upon fractionation of soil phosphorus. Soil Sci. Soc. Amer. Prac. 28: 218-224.

Allaway, W. H. and H. F. Rhoades. 1951. Forms and distribution of phosphorus in horizons of Nebraska soil in relation to profile development. Soil Sci. 72: 119-128.

Amer, F., D. R. Bouldin, C..A. Black, and F. R. Duke. 1955. Characterization of soil phosphorus by anion-exchange resin adsorption and p32equilibrium. PI. Soil. 6: 391-408.

Baker, R. T. 1976. Changes in the chemical nature of soil organic phosphate during pedogenesis. J. of Soil Sci. 27(4):504-512.

Bates, J. A. R., and T. C. N. Baker. 1960. Studies on a Nigerian forest soil. 11. The distribution of phosphorus in the profile and the various soil fractions. J. of Soil Sci. 11(2):257-265.

Bhangoo, M. S. and F. W. Smith. 1957. Fractionation of phosphorus in Kansas soils and its significance in response of wheat to phosphate fertilizers. Agron. J. 49: 354-358.

Birchett, John Robert. 1974. Plant-available and chemically extractable P in selected Iowa soil profiles developed in deep loess. PhD dissertation, Iowa State University Library, Ames, Iowa.

Bishop, W. D. and S. A. Barber. 1959. The effect of soil phosphorus.compounds on soil test correlation. Soil Sci. Soc. Amer. Proc. 23: 458-460.

Blanchar, R. W. and A. C. Caldwell. 1964. Phosphorus uptake by plants and readily extractable phosphorus in soils. Agron. J. 56: 218-221.

Bloomfield, C. 1981. The translocation of metals in soils. Pp. 463-504. In D. J. Greenland and M. H. B. Hayes (eds.) The chemistry of soil processes. John Wiley and Sons, New York.

Bray, R. H. and L. T. Kurtz. 1945. Determination of total, organic, and available forms of phosphorus in soils. Soil Sci. 59: 39-45.

Brinkman, R. 1970. Ferrolysis, a hydromorphic soil forming process. Geoderma 3:199-206.

Brinkman, R., A. G. Jongmans, R. Miedema, and P. Maas Kant. 1973. Clay decomposition in seasonally wet, acid soils: Micromorphological, chemical, and mineralogical evidence from individual argillans. Geoderma 10:259-270.

Bromfield, S. M. 1967. An examination of ammonium fluoride as a selective extractant for aluminum-bound phosphate in partially phosphated systems. Austr. J. Soil Res. 5:225-234. Brown, M. D.,

Chai, M. C. and A. C. Caldwell. 1959. Forms of phosphorus and fixation in soils. Soil Sci. Soc. Amer. Proc. 23: 458-460.

Chang, S. C. and A. S. R. Juo. 1963. Soil phosphorus fractions in relation to the forms of P in the soils. Soil Sci. 95: 91-96.

Chang, S. H. and W. K. Chu. 1961. The fate of soluble phosphate applied to soils. J. Soil Sci. 2: 277-293.

Chang, S. H. and M. L. Jackson. 1957. Fractionation of soil phosphorus. Soil Sci. 84: 133-144.

Chang, S. H. and M. L. Jackson. 1958. Soil phosphorus fractions in some representative soils. J. Soil Sci. 9:109-119.

Chang, S. C., and M. L. Jackson. 1958. Soil phosphorus fractions in some representative soils. J. Soil Sci. 9:109-119.

Chauhan, B. S., J. W. B. Stewart, and E. A. Paul. 1979. Effect of I carbon additions on soil labile inorganic, organic, and microbially held phosphate. Can. J. Soil Sci. 59:387-396.

Chauhan, B. S., J. W. B. Stewart, and E. A. Paul. 1981. Effect of labile inorganic phosphate status and organic carbon additions on the microbial uptake of phosphorus in soils. Can. J. Soil Sci. 61:373-385.

Cole, C. V., G. S. Innis, and J. W. B. Stewart. 1977. Simulation of P cycling in semiarid grasslands. Ecology 58:1-15.

Coleman, T. L. 1980. The influence of stratigraphy and landscape position on the genesis of upland loess-derived soils of southern Iowa. Unpublished Ph.D. dissertation. Iowa State University, Ames, Iowa.

Collins, M. E. 1977. Comparison of soil survey techniques in Tama County, Iowa, 1905, 1950, 1977. Unpublished M.S. thesis. Iowa State University, Ames, Iowa.

Cosgrove, D. J. 1977. Microbial transformations in the phosphorus cycle. <u>In</u> M. Alexander (ed.) Advances in microbial ecology. Vol. 1. Plenum Press, New York.

Dahnke, W. C., J. L. Malcolm, and M. E. Menendez. 1964. Phosphorus fractions in selected soil profiles of El Salvador as related to their development. Soil Sci. 98:33-38.

Dalal, R. C., 1977. Soil organic phosphorus. Adv. Agron. 29:83-113 1980.

DeConinck, F. 1980. Major mechanisms in the formation of spodic horizons. Geoderma 24:101-128.

Dennis, E. J. and L. Chesnin. 1953. Availability of phosphorus to alfalfa in the horizons of four eastern Nebraska soils. Soil Sci. Soc. Amer. Proc. 17: 49-52.

Dick, W. A., and M. A. Tabatabai. 1977. An alkaline oxidation method for determination of total phosphorus in soils. Soil Sci. Soc. Am. J. 41:511-514.

Dormaar, J. F. 1972. Seasonal patterns of soil organic phosphorus. Can. J. Soil Sci. 52:107-112.

Douchafour, P. 1982. Pedology. George Allen and Unwin, London.

Eik, K., J. R. Webb, C. A. Black, C. M. Smith, and J. T. Pesek. 1961. Evaluation of residual effects of phosphate fertilization by labora tory and plant-response methods. Soil Sci. Soc. Amer. Proc. 25: 21-24.

Eidt, R. C. 1977. Detection and examination of anthrosols by phosphate analysis. Science 197:1327-1333.

- Farmer, V. C. 1981. Possible roles of a mobile hydroxy aluminum orthosilicate complex (proto-imogolite) and of hydroxy aluminum and hydroxy iron species in podzolization. In Migrations organo-minerales dans les soils temperes. Proc. Coll. Inter. du CNRS (1979) No. 303.
- Fenton, T. E. 1966. Soils, weathering zones, and landscapes in the upland loess of Tama and Grundy Counties, Iowa. Unpublished Ph.D. dissertation. Iowa State University, Ames, Iowa.
- Fenton, T. E., F. F. Riecken, and J. F. Seaholm. 1967. Effect of vegetation on total phosphorus distribution in some Iowa soils. Agron. Abstr., p. 117.
- Fife, C. V. 1959a. An evaluation of ammonium flouride as a selective extractant for aluminum-bound soil phosphate: 1. Preliminary studies on non-soil systems. Soil Sci. 87:13-21.
- Fife, C. V. 1959b. An evaluation of ammonium flouride as a selective extractant for aluminum-bound soil phosphate: II. Preliminary studies on soils. Soil Sci. 87:83-88.
- Fife, C. V. 1962. An evaluation of ammonium flouride as a selective extractant for aluminum-bound soil phosphate: Ill. Detailed studies on selected soils (1). Soil Sci. 93:113-123.
- Flaig, W., H. Beutelspacher, and E. Rietz. 1975. Chemical composition and physical properties of humic substances. In J. E. Geiseking (ed.) Soil components. Vol. 1. Springer-Verlag, New York.
- Godfrey, C. L. 1951. Distribution and nature of phosphorus in a geochronosequence of loess-derived soils. Unpublished Ph.D. dissertation. Iowa State University, Ames, Iowa.
- Godfrey, C. L., and F. F. Riecken. 1957. Solubility of phosphorus in some genetically related loess-derived soils. Soil Sci. Soc. Am. Proc. 21:232-235.
- Greenland, D. J. 1971. Interactions between humic acid and fulvic acid Soil Sci. 111(1):34-39.
- Griffin, R. A., and J. J. Jurinak. 1973. Test of a new model for the kinetics of adsorption-desorption processes. Soil Sci. Soc. Am. Proc. 37:869-872.
- Godfrey, C. L. and F. F. Riecken. 1954. Distribution of phosphorus in some genetically related loess-derived soils. Soil Sci. Soc. Amer. Proc. 18: 80-84.
- Godfrey, C. L. and F.F. Riecken. 1957. Solubility of phosphorus in some genetically related loess-derived soils. Soil Sci. Soc. Amer. Proc. 21: 232-235.
- Haseman, J. F., E. H. Brown, and C. D. Whitt. 1950. Some reactions of phosphate with clays and hydrous oxides of iron and aluminum. Soil Sci. 70:257-271.
- Hawkins, R. H., and G. W. Kunze. 1965. Phosphate fractions in some Texas Grumusols and their relation to soil weathering and available phosphorus. Proc. Soil Sci. Soc. Am. 29:650-656.
- Hayes, M. H. B., and R. S. Swift. 1978. The chemistry of soil colloids. <u>In</u> D. J. Greenland and M.H.B. Hayes (eds.) The chemistry of soil constituents. John Wiley and Sons, New York.
- Haider, K., and J. P. Martin. 1981. Biochemistry of humus formation and its interactions with clays. In Migrations organo-minerales dans les soil temperes. Proc. Coll. Inter. du CNRS (1979) No. 303.
- Halstead, R. L., A. J. Maclean, and L. E. Lutwick. 1956. Availability of phosphorus in soils pretreated with superphosphate. Can. J. Agr. Sci. 36: 471-482.

Hedley, M. J., J. W. B. Stewart, and B. S. Chauhan. 1982. Changes in inorganic and organic soil phosphorus fractions induced by cultivation practices and laboratory incubations. Soil Sci. Soc. Am. J. 46:970-976.

Hobson, W. E. 1983. Inorganic phosphorus fractions and humic acid carbon to fulvic acid carbon ratios as differentiae for selected Alfisols and Mollisols. Unpublished Ph.D. dissertation. Iowa State University, Ames, Iowa.

Hooker, M. L., G. A. Peterson, D. H. Sander, and L. A. Daigger. 1980. Phosphate fractions in calcareous soils as altered by time and amounts of added phosphate. Soil Sci. Soc. Am. J. 44:269-277.

Hsu, P. H. and M. L. Jackson. 1960. Inorganic phosphorus transformations by chemical weathering in soils as influenced by pH. Soil Sci. 90: 16-23.

Huddleston, J. H. 1969. Local soil-landscape relationships in eastern Pottawattamie County, Iowa. Unpublished Ph.D. thesis. Library, Iowa State University, Ames, Iowa.

Hutton, C. E. 1948. The morphology and genesis of prairie soils from peorian loess in southwestern Iowa. Unpublished Ph.D. thesis. Library, Iowa State University, Ames, Iowa.

Islam, A., and R. Mandal. 1977. Amounts and mineralization of organic phosphorus compounds and derivatives in some surface soils of Bangladesh. Geoderma 17:57-68.

Jackson. M. L. 1958. Soil chemical analysis. Ist ed. Prentice Hall Inc., Englewood Cliffs, N.J.

John,, M. K. 1970. Colormetric determination of phosphorus in soil and plant material with ascorbic acid. Soil Sci. 109: 214-220.

Jungerius, P. D. 1969. Soil evidence of post glacial treeline fluctuations in the Cypress Hills area, Alberta, Canada. Arctic and Alpine Res. 1:235-245.

Juo, A. S. R., and B. G. Ellis. 1968. Chemical and physical properties of iron and aluminum phosphates and their relation to phosphorus availability. Soil Sci. Soc. Am. Proc. 32:216-221.

Kao, C. W., and R. W. Blanchar. 1973. Distribution and chemistry of phosphorus in an Albaqualf soil after 82 years of phosphorus fertilization. J. Environ. Qual. 2(2):237-240.

Kazemi, Masoud. 1983. Interrlationships among biosequences, available phosphorus distribution, and other soil variables in Eastern Iowa. Unpublished M.S. thesis. Library, Iowa State University, Ames, Iowa.

Khan, S. V. 1969. Interaction between the humic acid fraction of soils and certain metallic cations. Soil Sci. Soc. Am. Proc. 33:851-854.

Kosse, A. D. 1966. Organic phosphorus/organic carbon ratios and natural drainage class in soils. Unpublished M.S. thesis. Iowa State University, Ames, Iowa.

Kowalenko, C. G., and R. B. McKercher. 1971. Phospholipid components extracted from Saskatchewan soils. Can. J. Soil Sci. 51:19-22.

Kyle, J. H., A. M. Posner, and J. P. Quirk. 1975. Kinetics of isotopic exchange of phosphate adsorbed on gibbsite. J. Soil Sci. 26(1):32-43.

Larsen, S. 1967. Soil phosphorus. Adv. in Agron. 19:151-206.

Lehman, D. S. 1963. Some principles of chelation chemistry. Soil Sci. Soc. Am. Proc. 27:167-170.

Lindsay, W. L. 1979. Chemical equilibria in soils. John Wiley and Sons, New York.

Lindsay, W. L., and E. C. Moreno. 1960. Phosphate phase equilibria in soils. Soil Sci. Soc. Am. Proc. 24:177-182.

Lindsay, W. L., and P. L. Vlek. 1977. Phosphates. Pp. 639-670. J. B. Dixon and S. B. Weed (eds.) Minerals in soil environments. Soil Sci. Soc. of Am., Madison, Wisconsin.

Mattingly, G. E. G. 1975. Labile phosphate in soils. Soil Sci. 119(5):369-375.

Mausbach, M. J. 1969. Inorganic phosphorus fractions in some Iowa soil profiles. Unpublished M.S. thesis. Iowa State University, Ames,

McGill, W. B., and C. V. Cole. 1981. Comparative aspects of cycling of C, N, S, and P through soil organic matter. Geoderma 26:267-286.

McLaughlin, J. R., J. C. Ryden, and J. K. Svers. 1977. Development and evaluation of a kinetic model to describe phosphate sorption by hydrous ferric oxide gel. Geoderma 18:295-307.

Miller, G. A. 1974. Soil parent material, stratigraphy and soil development, Cedar County, Iowa. Unpublished Ph. D. dissertation, Library, Iowa State University, Ames, Iowa.

Miller, R. B. 1968. Flows and cycles of macro- and micro-elements in a forest soil and its environment. Trans. 8th Inter. Cong. Soil Sci. 4:323-331.

Murdock, J. T. and L. E. Engelbert. 1957. The importance of subsoil phosphorus to corn. Northcentral Regional Phosphorus Report 1957: 81-85.

Murphy, J. and J. P. Riley. 1962. A modified single solution method for the determination of phosphate in natural waters. Anal. Chim. Acta 27: 31-36.

Murrmann, R. P. and M. Peech. 1969. Relative signifiance of labile and crystalline phosphates in soil. Soil Sci. 107: 249-255.

Novak, L. T., D. C. Adreano, G. A. Coulman, and D. B. Shah. 1975. P movement in soils: Theoretical aspects. J. Environ. Qual. 4(1):93-99.

Nriagu, J. 0. 1976. Phosphate-clay mineral relations in soils and sediments. Can. J. Earth Sci. 13(6):717-736,

Olsen, S. R., F. S. Watanabe, and R. A. Bowman. 1983. Evaluation of fertilizer phosphorus residues by plant uptake and extractable phosphorus. Soil Sci. Soc. Am. J. 47:952-958.

Olson, R. A. and M. T. Rhodes. 1953. Calibration of soil tests for phosphorus with A value and yield response data. Northcentral Region Phosphorus Report 1953: 105-110.

Olson, R. A. and R. C. Sorenson. 1957. The subsoil and series factors in Nebraska soil testing. Northcentral Region Phosphorus Report 1957: 76-80.

Oschwald, W. H., F. F. Riecken, R. I. Dideriksen, W. H. Scholtes, and F. W. Schaller. 1965. Principal soils of Iowa. Iowa Coop. Ext. Serv. Spec. Rpt. #42.

Parfitt, R. L., R. J. Atkinson, and R. St. C. Smart. 1975. The mechanisms of phosphate fixation by iron oxides. Soil Sci. Soc. Am. Proc. 39:837-841.

Paton, T. R. 1978. The formation of soil material. George Allen and Unwin, London.

Payne, H. and W. J. Hanna. 1965. Correlations among soil phosphorus, extractable phosphorus, and plant content of phosphorus. J. Agr. Food Chem. 13: 322-326.

Pearson, R. W., R. Spry, and W. H. Pierre. 194O. The verticle distribution of total and dilute acid-soluble phosphorus in twelve Iowa soil profiles. Jour. Amer. Soc. Agron. 32: 683-696.

Petersen, G. W., and R. B. Corey. 1966. A modification of the Chang and Jackson procedure for routine fractionation of inorganic soil P Soil Sci. Soc. Am. Proc. 30:563-565.

Pettapiece, W. W. 1969. The forest grassland transition. Pp. 103-113. In S. Pawluk (ed.) Pedology and Quaternary research. Univ. Alberta Printing Office, Edmonton, Alberta.

Plaisance, G., and A. Cailleux. 1958. Dictionary of soils. LaMaison Rastique Publishers, Paris. Published for USDA and the National Sci. Foundation by Amerind Pub. Co. Pvt. Ltd., New Delhi, 1981.

Probert, M. E., and S. Larsen. 1972. The kinetics of heterogeneous isotopic exchange. J. Soil Sci. 23(1)76-81.

Puranik, R. B., N. K. Barde, and D. K. Ballal. 1979. Soil phosphorus as an index of weathering. In Phosphorus in soils, crops, and fertilizers. Indian Soc. of Soil Sci., New Delhi.

Phoorata, P. 1971. Availability of native and added phosphorus in Iowa soils. Unpublished M.S. thesis. Library, Iowa State University, Ames, Iowa.

Pratt, P. F. and M. J. Garber. 1964. Correlations of phosphorus availability by chemical soil tests with inorganic phosphorus fractions. Soil Sci. Soc. Amer. Proc. 28: 23-26.

Quereshi, R. H., D. A. Jenkins, and R. 1. Davies. 1978. Electron probe microanalytical studies of phosphorus distribution within soil fabric. Soil Sci. Soc. Am. J. 42:698-703.

Riecken, F. F., and E. Poetsch. 1960. Genesis and classification considerations of some prairie-formed soil profiles from local alluvium in Adair County, Iowa. Proc. Iowa Acad. Sci. 67:277-289.

Ruhe, R. V., and W. H. Scholtes. 1956. Age and development of soil landscapes in relation to climatic and vegetational changes in Iowa. Soil Sci. Soc. Am. Proc. 20:264-273.

Ruhe, R. V., T. E. Fenton, and L. L. Ledesma. 1975. Missouri River history, floodplain construction, and soil formation in Southwestern Iowa. Iowa Agric. and Home Econ. Exp. Stn. Res. Bull. 580.

Ruhe, R. V. 1969. Quaternary landscapes in Iowa. The Iowa State University Press, Ames, Iowa.

Runge, E. C. A. 1963. Influence of natural drainage on iron and phosphorus distribution in some Iowa soils. Unpublished Ph.D. thesis. Library, Iowa State University, Ames, Iowa.

Runge, E. C. A., and F. F. Riecken. 1966. Influence of natural drainage on distribution of phosphorus in some Iowa prairie soils. Soil Sci. Soc. Am. Proc. 30:624-630.

Ryan, J., and M. A. Zghard. 1979. Phosphorus transformations with age in a calcareous soil chronosequence. Soil Sci. Soc. Am. J. 44:168-169.

Ryden, J. C., and J. K. Syers. 1977. Origin of the labile phosphate pool in soils. Soil Sci. 123(6):353-361.

Ryden, J. C., J. R. McLaughlin, and J. K. Syers. 1977. Mechanisms of phosphate sorption by soils and hydrous ferric oxide gel. J. Soil Sci. 28:72-92.

Sanchez, A. 1955. The phosphorus supplying power of some N.Y. soils as determined by pot and chemical methods. Unpublished Ph.D. thesis. Library, Cornell University, Ithica, New York.

Schnitzer, M. 1978. Humic substances: Chemistry and reactions. Pp. 1-58. <u>In M. Schnitzer and S. V. Khan (eds.)</u> Soil organic matter. Elsevier Pub. Co., New York.

Schnitzer, M. 1981. Reactions of humic substances with metals and minerals in soils. <u>In Migrations organominerales dans les soils temperes</u>. Proc. Coll. Inter. du CNRS (1979) No. 303.

Sekhon, G. S., and C. A. Black. 1969. Changes in extractable organic phosphorus in soil in the presence and absence of plants. Plant Sci. 31:321-327.

Smeck, N. E. 1970. Factors influencing development of Mollic Albaqualfs: Comparison within and between two soil development sequences in Illinois. Unpublished Ph.D. dissertation. University of Illinois, Urbana, Illinois.

Smeck, N. E. 1973. Phosphorus: An indicator of pedogenetic weathering processes. Soil Sci. 115(3):199-206.

Smeck, N.E. 1985. Phosphorus dynamics in soils and landscapes. Geoderma 36: 185-199.

Smeck, N.E. and E.C.A. Runge. 1971. Phosphorus availability and redistribution in relation to profile development in an Illinois landscape segement. Soil Sci. Soc. Am. Proc., 35: 952-959.

Smith, G. D., W. H. Allaway, and F. F. Riecken. 1950. Prairie soils of the upper Mississippi valley. Adv. Agron. 2:157-205.

Smith, A. N. 1965. The supply of soluble phosphorus to the wheat plant from inorganic soil phosphorus. Pl. Soil 22: 314-316.

Smith, F. W., B. G. Ellis, and J. Grava. 1957. Use of acid fluoride solutions for the extraction of available phosphorus in calcareous soils and in soils to which rock phosphate has been added. Soil Sci. Soc. Amer. Proc. 21: 400-404.

Stanford, G. and J. D. DeMent. 1957. A method for measuring short term absorption by plants. I. Phosphorus. Soil Sci. Soc. Amer. Proc. 21: 612-617.

SteIly, M. 1942. Forms of inorganic phosphorus in the lower horizons of some Iowa soils as indicated by plant availability and chemical methods. Unpublished Ph.D. thesis. Library, Iowa State University, Ames, Iowa.

Stelly, M. and W. H. Pierre. 1943. Forms of inorganic phosphorus in the C horizon of some Iowa soils. Soil Sci. Soc. Amer. Proc. 7: 139-147.

Susuke, A., K. Lawton, and E. C. Doll. 1963. Phosphorus uptake and soil tests as related to forms of phosphorus in some Michigan soils. Soil Sci. Soc. Amer. Proc. 27: 401-403.

Swindale, L. D., and M. L. Jackson. 1956. Genetic processes in some residual podzolized soils of New Zealand. Trans. 6th Inter. Congr. Soil Sci., Paris, E:233-239.

Syers, J. K., J. D. H. Williams, A. S. Campbell, and T. W. Walker. 1967. The significance of apatite inclusions in soil phosphorus studies. Soil Sci. Soc. Am. Proc. 31:752-756.

Tamhane, R. V. 1962. Correlations of soil tests with pot and field trials in the evaluation of soil fertility. Soil Sci. Pl. Nutr. 8: 97-106.

Tembhare, B. 1973. Available and inorganic forms of phosphorus in selected Alfisols and Mollisols. Unpublished Ph.D. dissertation. Iowa State University, Ames, Iowa.

Theng, B. K. G. 1979. Formation and properties of clay-polymer complexes Elsevier Pub. Co., New York.

Tiessen, H., J. W. B. Stewart, and C. V. Cole. 1983. Pedogenic pathways of P cycling in North American soils. Agron. Abstr., 1983:151.

Tiessen, H., Stewart, J.W.B. and Cole, C.V. 1984. Pathways of phosphorus transformations in soils of differing pedogenesis. Soil Sci. Soc. Am. J 48: 853-858.

Tripathi, B. R., H. L. S. Tandon, and E. H. Tyner. 1970. Native inorganic phosphorus forms and their relation to some chemical indicies of phosphate availability for soils of Agra district, India. Soil Sci. 109: 93-101.

Truog E. 1930. The determination of the readily available phosphorus of oils. Amer. Soc. Agron. J. 22: 281-298.

Udo, E. J. 1977. Forms and distribution of phosphorus in three Nigerian soil profiles along a toposequence. Tropical Agric. 54(2):149-156.

Uzu, F. O., A. S. R. Juo, and A. A. A. Fayemi., 1975. Forms of phosphorus in some important agricultural soils in Nigeria. Soil Sci. 120:212-218.

Vaidyanathan, L. V., and P. H. Nye. 1966. The measurement and mechanisms of ion diffusion in soils. J. Soil Sci. 17(2):175-183.

Vaidyanathan, L. V., and 0. Talibudeen. 1970. Rate processes in the desorption of phosphate from soils by ion-exchange resins. J. Soil Sci. 21(l):173-183.

van Riemsdijk, W. H., F. A. Westrate, and G. H. Bolt. 1975. Evidence for a new aluminum phosphate phase from reaction rate of phosphate with aluminum hydroxide. Nature 257:473-474.

Walker, T. W. 1964. The significance of phosphorus in pedogenesis. Pp. 295-316. <u>In</u> Experimental pedology. William Clowes and Sons, Ltd., London,

Walker, T. W., and J. K. Syers. 1976. The fate of phosphorus during pedogenesis. Geoderma 15:1-19.

Watanabe, F. S. and S. R. Olsen. 1966. Test of an ascorbic acid method for determining phosphorus in water and NaHCO3 extracts from soil. Soil Sci. Soc. Amer. Proc. 29: 677-678.

Weaver, R. M. 1974. A simplified determination of reductant-soluble phosphate in soil phosphate fractionation schemes. Soil Sci. Soc. Am. Proc. 38:153-154.

Welch, L. F., L. E. Ensminger, and C. M. Wilson. 1957. Correlation of soil phosphorus with yields of ladino clover. Soil Sci. Soc. Amer. Proc. 21: 618-620.

Westin, F. C. and G. J. Bunting. 1966. Soil phosphorus in South Dakota: II. Comparisons of two availability tests with inorganic phosphorus fractions among soil series. Soil Sci. Soc. Amer. Proc. 30: 248-253.

Westin, F. C., and G. J. Buntley. 1967. Soil phosphorus in South Dakota: III. Phosphorus fractions of some Borolls and Ustolls. Soil Sci. Soc. Am. Proc. 31:521-528.

Westin, F. C., and J. G. deBrito. 1969. Phosphorus fractions of some Venezuelan soils as related to their stage of weathering. Soil Sci. 107:194-202.

White, E. M. 1953. The genesis and morphology of some transitional brunizem-gray brown podzolic soils. Unpublished Ph.D. dissertation. Iowa State College, Ames, Iowa.

Williams, E. B., and W. M. H. Saunders. 1956. Distribution of phosphorus in profiles and particle-size fractions of some Scottish soils. J. Soil Sci. 7:90-108.

Williams, J. D. H., and T. W. Walker. 1969a. Fractionation of phosphate in a maturity sequence of New Zealand basaltic profiles: 1. Soil Sci. 107:22-29.

Williams, J. D. H., and T. W. Walker. 1969b. Fractionation of phosphate in a maturity sequence of New Zealand basaltic profiles: 2. Soil Sci. 107:213-219.

Williams, J. D. H., T. Mayer, and J. 0. Nriagu. 1980. Extractability of phosphorus from phosphate minerals common in soils and sediments. Soil Sci. Soc. Am. J. 44:462-465.

Williams, J. D. H., J. K. Syers, and T. W. Walker. 1967. Fractionation of inorganic phosphate by a modification of Chang and Jackson's procedure. Soil Sci. Soc. Am. Proc. 31:736-739.

Worcester, B. K. 1973. Soil genesis on the stable primary divides of the southwestern loess provence. Unpublished Ph.D. thesis. Library, Iowa State University, Ames, Iowa.

Zubriski, J. C., E. B. Norum, and D. Q. Posin. 1953. Comparison of phosphorus A values with chemical soil tests for soil phosphorus on 40 North Dakota soil samples. Northcentral Region Phosphorus Report 1953:102-105,